

Thermaltake Smart RGB power supply unit 600 W 20+4 pin ATX ATX Black



Model: PS-SPR-0600NHSWE-1

Manufacturer: THERMALTAKE

EAN: 4711246870468

Product Code: 1339160

R1,816

Hold time: 16 ms | Floppy disk drive cable length: 10 cm | Max output current (+5V): 17 A | ATX power connector (20+4 pin): Yes | Combined power (-12V): 6 W | Fan location: Top | Combined power (+5Vsb): 12.5 W | Max output current (+5Vsb): 2.5 A | CPU power connector (4+4 pin): Yes | Combined power (+5V): 105 W | PCI Express power connectors (6+2 pin): 2 | Number of SATA power connectors: 5 | Power Factor Correction (PFC) type: Active | Combined power (+12V): 504 W | Max output current (+3.3V): 22 A | PCI Express connector: Yes | CPU power cable length: 55 cm | Motherboard power cable length: 50 cm | Floppy drive power connector: 1 | Combined power (+3.3V): 105 W | Max output current (+12V): 42 A | Max output current (-12V): 0.5 A | Power Good signal delay range: 100 - 500 ms | Motherboard power connector: 20+4 pin ATX | ATX version: 2.3 | Operating temperature (T-T): 5 - 40 °C | Harmonized System (HS) code: 84733020 | Peripheral (Molex) power connectors (4-pin): 4 | Floppy disk drive connector: Yes | Illumination colour: Multi |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Noise level: 28.1 dB | Cabling type: Non-Modular | Width: 150 mm | Purpose: PC | Product colour: Black | Power supply unit (PSU) form factor: ATX | Cooling type: Active | Total power: 600 W | AC input voltage: 230 V | Depth: 140 mm | Mean time between failures (MTBF): 100000 h | Storage temperature (T-T): -40 - 55 °C | Efficiency: 86% | Height: 86 mm | Safety: CE/CB/TUV/ EAC | AC input frequency: 50 - 60 Hz | Number of fans: 1 fan(s) | Input current: 7 A | 80 PLUS certification: 80 PLUS | Operating relative humidity (H-H): 20 - 85% | Storage relative humidity (H-H): 10 - 95% | Illumination: Yes | Package type: Box | Fan diameter: 12 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950