

Thermaltake Smart RGB power supply unit 700 W 20+4 pin ATX ATX Black



Model: PS-SPR-0700NHSWE-1

Manufacturer: THERMALTAKE

EAN: 4711246870475

Product Code: 1339161

R2,023

Hold time: 16 ms | Product colour: Black | Storage temperature (T-T): -40 - 55 °C | Power supply unit (PSU) form factor: ATX | Operating temperature (T-T): 5 - 40 °C | Efficiency: 86% | CPU power connector (4+4 pin): Yes | ATX power connector (20+4 pin): Yes | Combined power (-12V): 6 W | Combined power (+5V): 120 W | Motherboard power cable length: 50 cm | AC input voltage: 230 V | Input current: 9 A | Max output current (+5V): 17 A | Combined power (+3.3V): 120 W | Floppy disk drive cable length: 10 cm | Max output current (+5Vsb): 2.5 A | Illumination colour: Multi | Cooling type: Active | Safety: CE/CB/TUV/ EAC | Max output current (+12V): 54 A | Combined power (+5Vsb): 12.5 W | Floppy disk drive connector: Yes | PCI Express connector: Yes | Storage relative humidity (H-H): 10 - 95% | Illumination: Yes | Mean time between failures (MTBF): 100000 h | PCI Express power connectors (6+2 pin): 2 | Max output current (+3.3V): 24 A | Combined power (+12V): 648 W | Power Factor Correction (PFC) type: Active | 80 PLUS certification: 80 PLUS | Number of SATA power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

connectors: 6 | Harmonized System (HS) code: 84733020 | Package type: Box | AC input frequency: 50 - 60 Hz | Peripheral (Molex) power connectors (4-pin): 5 | Floppy drive power connector: 1 | Noise level: 28.1 dB | Number of fans: 1 fan(s) | CPU power cable length: 55 cm | Cabling type: Non-Modular | Operating relative humidity (H-H): 20 - 85% | Max output current (-12V): 0.5 A | Total power: 700 W | Power Good signal delay range: 100 - 500 ms | Fan diameter: 12 cm | Motherboard power connector: 20+4 pin ATX | Purpose: PC | Fan location: Top | ATX version: 2.3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950