

Thermaltake Smart BX1 power supply unit 550 W 24- pin ATX ATX Black



Model: PS-SPD-0550NNSABE-1

Manufacturer: THERMALTAKE

EAN: 4711246875227

Product Code: 1339162

R1,602

Total power: 550 W | Fan location: Top | PCI Express power connectors (6+2 pin): 2 | Combined power (+5Vsb): 12.5 W | Peripheral (Molex) power cable length: 500 mm | Peripheral (Molex) power cable length: 150 | Input current: 10 A | Efficiency: 88% | Max output current (-12V): 0.5 A | Floppy disk drive connector: Yes | PCI Express connector: Yes | Noise level: 37.6 dB | Purpose: PC | Depth: 140 mm | SATA power cable length: 150 | Max output current (+5Vsb): 2.5 A | Peak power: 660 W | EPS version: 2.92 | Number of SATA power connectors: 6 | Peripheral (Molex) power connectors (4-pin): 4 | Operating temperature (T-T): 5 - 40 °C | SATA power cable length: 500 mm | Power supply unit (PSU) form factor: ATX | Max output current (+12V): 38 A | Storage temperature (T-T): -40 - 55 °C | Max output current (+5V): 16 A | Product colour: Black | Combined power (-12V): 6 W | Motherboard power cable length: 60 cm | Cabling type: Non-Modular | Max output current (+3.3V): 21 A | Width: 150 mm | Combined power (+5V): 105 W | CPU power connector (4+4 pin): Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Cooling type: Active | Combined power (+3.3V): 105 W | Height: 86 mm | Hold time: 16 ms | AC input voltage: 230 V | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | AC input frequency: 50 Hz | Floppy drive power connector: 1 | CPU power cable length: 65 cm | Storage relative humidity (H-H): 10 - 95% | Illumination: No | Combined power (+12V): 456 W | Power Factor Correction (PFC) type: Active | Safety: CE, CB, TUV, EAC, RCM | On/off switch: Yes | Operating relative humidity (H-H): 20 - 85% | ATX version: 2.3 | Fan diameter: 12 cm | Number of fans: 1 fan(s) | Motherboard power connector: 24-pin ATX | Maximum input current (@220V): 10 A | Power Good signal delay range: 100 - 500 ms

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950