

LOKITHOR J402 PRO 88.8 Wh 3500 A Jump Starter



Model: J402 PRO

Manufacturer: LOKITHOR

EAN: 6928493313152

Product Code: 1420146

R4,536

LOKITHOR J402 PRO Jump Starter 88.8Wh 3500A

The LOKITHOR J402 PRO is a compact, high-current jump starter—up to 3500A—designed for 12V vehicles, capable of effortlessly starting gasoline engines up to 9.5L and diesel engines up to 7.5L. Equipped with 100W bidirectional fast charging, a power bank function, a high-capacity 88.8Wh battery, and advanced safety features, it ensures convenience and safety of use. Thanks to its short charging time (approx. 0.9–1.4 hours), long standby mode, built-in LED flashlight, and durable, compact housing with IP65 protection, it performs well both in everyday use and in emergency situations.

Powerful starting even for large engines

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The device offers high starting current, allowing you to quickly start vehicles with a 12V system, including passenger cars, motorcycles, and boats. It supports gasoline engines up to 9.5 liters and diesel engines up to 7.5 liters, making it suitable for both everyday vehicles and more demanding applications.

100W fast charging and power bank function

The J402 PRO model offers fast charging up to 100W, allowing you to efficiently recharge the device itself and conveniently charge connected mobile devices. USB-A and USB-C ports enable charging of smartphones, tablets, headphones, and other mobile devices, making it a practical solution not only in the car but also while traveling.

Advanced safety features and full control

The device is equipped with an intelligent battery management system that continuously monitors voltage and operating parameters. Built-in safety features protect against reverse connection, short circuits, overcharging, overcurrent, overheating, and excessively high or low voltage. The warning system alerts you to any potential issues, enhancing safety during use.

Long standby time and fast charging

The low-self-discharge cells used allow the device to remain on standby for a long time without the need for frequent charging. A full charge takes less than 1.5 hours (approx. 55-85 minutes), allowing you to quickly prepare the equipment for operation when needed.

Compact and durable design

Its compact dimensions (240.3 × 106.5 × 60 mm) and sturdy housing make the device convenient to store and transport. The design is built for durability and resistance to daily use, and the IP65 rating provides protection against dust and splashes.

Additional features and accessories

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The built-in 300-lumen LED flashlight offers three lighting modes, making it easier to use the device after dark or in emergency situations. The kit includes all necessary accessories, including USB cables (USB-A to USB-C and USB-C to USB-C), a 12V adapter, and a user manual, so the device is ready to use right out of the box.

Included

- Jump starter
- USB-C to USB-C cable
- USB-A to USB-C cable
- 12V adapter
- Engine jump leads
- Accessory pouch

Model	J402 PRO
Dimensions (L x W x H)	240.32 x 106.5 x 60 mm
Suitable engine capacity	Up to 9.5L gasoline / 7.5L diesel
Capacity	88.8 Wh (6000 mAh)
Clamps	Red (+), Black (-)
Starting current	2250A
Peak current	3500A
Input (Input)	DC: 12V=5A (60W MAX); USB-C: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A (100W MAX)
Output	USB-A: 5V=3A, 9V=2A, 12V=1.5A (18W MAX); USB-C: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A (100W MAX)
Start-up voltage	12V
Charging Temperature	0 °C to 45 °C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating Temperature	-20 °C to 50 °C
Storage Temperature	-20 °C to 50 °C
Charging Time	0.9 ~ 1.4 hours
Lifespan	>1000 cycles (under optimal conditions)
LED light	300 lumens, 3 modes

IP protection class IP65

Voltage (V): 12, Capacity (mAh): 6000, Cechy dodatkowe: Ładowanie smartfonów, Current (A): 3000, GPSR Link: https://psr-assets.innpro.pl/car_accessories/sg_car_accessories_starting_devices.pdf, Gross weight: 1940, Net weight: 1930, Box length: 24,00, Box width: 13,50, Box height: 12,00, PPWR: <https://ppwr.innpro.pl/lokithor>