

TP-Link TL- WA1201 wireless access point 867 Mbit/s White Power over Ethernet (PoE)



Model: TL-WA1201

Manufacturer: TP-LINK

EAN: 1210002608510

Product Code: 1424057

R1,678

Compatible operating systems: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | Reset button: Yes | Antenna type: External | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | MIMO: Yes | DHCP client: Yes | 5 GHz: Yes | 2.4 GHz: Yes | Maximum data transfer rate: 867 Mbit/s | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Product colour: White | Ethernet LAN data rates: 1000 Mbit/s | Sustainability compliance: Yes | Output voltage: 12 V | Virtual LAN features: Multicast VLAN | 6 GHz: No | AC adapter included: Yes | Package depth: 255 mm | MIMO type: Multi User MIMO | Storage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | PoE adapter included: Yes | Output current: 1.5 A | Operating relative humidity (H-H): 10 - 90% | Access Control List (ACL): Yes | Maximum data transfer rate (5 GHz): 867 Mbit/s | Quantity per pack: 1 pc(s) | Package weight: 860 g | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Depth: 145.5 mm | Transmitting power (FCC): 30 dBm | WPS push button: Yes | Power over Ethernet (PoE) type supported: Active PoE | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): 0 - 40 °C | Compliance certificates: RoHS | Compliance certificates: CE | Transmitting power (CE): 20 - 23 dBm | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA | Placement: Table | Security algorithms: 128-bit WEP | Auto Wireless Distribution System (WDS): Yes | Compliance certificates: Federal Communications Commission (FCC) | On/off switch: Yes | Package width: 400 mm | VLAN support: Yes | Universal Plug and Play (UPnP): Yes | Security algorithms: WPA2-PSK | Power over Ethernet (PoE): Yes | Storage relative humidity (H-H): 10 - 90% | Package height: 69 mm | DHCP server: Yes | Width: 225 mm | Wi-Fi Multimedia (WMM)/(WME): Yes | Cables included: LAN (RJ-45) | Height: 37 mm | Security algorithms: WPA-PSK | Antennas quantity: 4 | Quick start guide: Yes | Service Set Identifier (SSID) features: Multiple SSIDs

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950