



Switch

MIKROTIK

CRS310-1G-5S-4S+IN Type L3

PoE ports 1

CRS310-1G-5S-4S+IN

Model: CRS310-1G-5S-4S+IN

Manufacturer: MIKROTIK

EAN: 4752224007827

Product Code: 1424524

R4,358

10 Gigabit fibre connectivity way over a 100 meters – for small offices or ISPs. Hardware offloaded VLAN-filtering and even some L3 routing on a budget!

This switch is an indoor variation of the prominent netFiber 9 switch – used by many small and medium ISPs for reliable 10 Gigabit fibre connections stretching over a 100 meters. With five 1G SFP ports, four 10G SFP+ ports, and an additional Gigabit Ethernet port, this is the perfect upgrade for existing CRS212 setups. You're getting the modern ARM v7 CPU, 256 MB of RAM, and better cooling. The new Marvell switch-chips bring phenomenal performance to the table!

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The Gigabit Ethernet port has a direct connection to the switch chip – so you can enjoy full gigabit speed there. And it supports PoE-in, giving you an additional powering option in tricky spots.

You can mount this switch in a standard 1U rack to keep everything organized. And it has all the power you would expect from a rackmount device: CRS310 supports hardware offloaded VLAN-filtering. And even some hardware offloaded Layer-3 routing.

CRS310-1G-5S-4S+IN is a fantastic tool for anyone working with indoor connections over 100 meters while keeping data loss and ping low. Optical fiber can be a great alternative to copper if you are worried about electromagnetic interference, tampering or eavesdropping.

Summary: Mikrotik CRS310-1G-5S-4S+IN. Switch type: Managed, Switch layer: L3. Console port: RJ-45. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 18 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage:

https://mikrotik.com/product/crs310_1g_5s_4s_in | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L3 | SFP modulio angų kiekis: 5 | SFP+ modulio angų kiekis: 4 | Konsolės prievadas: RJ-45 | Tinklo standartai: IEEE 802.3af/IEEE 802.3at | 10G parama: Taip | Stovo montavimas: Taip | Forma: 1U | Atstatymo mygtukas: Taip | Integruotas procesorius: Taip | Procesoriaus modelis: 98DX226S | Procesoriaus dažnis: 800 | Vidinė atmintis: 256 | Flash atmintis: 16 | Vidutinis laikas tarp trikčių (MTBF): 200000 | Maitinimo šaltinis: DC/PoE | Pridėtas maitinimo šaltinis: Taip | DC įėjimo įtampa: 18 - 57 | Galios suvartojimas (maks.): 20 | Maitinimas per Eternetą (PoE): Taip | Darbo temperatūros diapazonas (TT): -40 - 70 | Plotis: 200 | Ilgis: 166 | Aukštis: 45 | Sertifikavimas: CE, EAC, ROHS | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 1.04 | Neto svoris: 0.9 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 20 | Shipping Box Height: 6 | Vieneto gylis: 31.5 | Vieneto aukštis: 6 | Name: NET ROUTER/SWITCH 9PORT/CRS310-1G-5S-4S+IN MIKROTIK | Model name: CRS310-1G-5S-4S+IN