Case LIAN LI ATX/micro ATX/Mini-ITX/EATX/SSI EEB Black Midi Tower PC Lian Li Lancool 217 INF Black (G99.LAN217INFX.00) G99.LAN217INFX.00

Model: G99.LAN217INFX.00

Manufacturer: LIAN LI

EAN: 4718466020642

Product Code: 1424617

R3,342

Корпус Lian Li Lancool 217 INF Black (G99.LAN217INFX.00)

Infinity Mirror, Now Breathing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

LANCOOL 217 INF continues our signature high-efficiency airflow design with an infinity mirror front panel for a striking visual effect, while dual tempered glass cutouts ensure ample airflow.

INNOVATIVE DESIGN AVAILABLE IN TWO COLORS

LANCOOL 217 INF comes in black and white, ensuring a perfect match with any setup style. With pre-installed RGB fans and infinity lighting, it delivers a unified and visually striking look.

INFINITY MIRROR, TOTAL CONTROL

With L-Connect 3, users can wirelessly control fan speed and ARGB lighting, including the front panel’s infinity mirror. When paired with the L-Wireless controller, it delivers synchronized lighting effects across compatible devices for a seamless and immersive setup.

LIGHTING CONTROL, MADE SIMPLE

The top I/O panel integrates an M1 button for front panel lighting and an M2 button for fan lighting effects, allowing easy customization of illumination styles.
Users can choose between three lighting control methods: through L-Connect 3 (wireless controller required), via the I/O buttons, or by using motherboard sync.

After switching to wireless mode, users can customize LANCOOL 217 INF’s lighting effects and fan speeds through L-Connect 3, creating their own seamless wireless ecosystem. The dual-zone lighting control allows users to adjust the lighting of the fans and the infinity mirror together or separately for a more personalized setup.

In default mode, both 170 mm and 140 mm fans run via PWM sync with the motherboard. In wireless mode, L-Connect 3 enables independent control of fan speed and lighting for a customized setup.

MASSIVE AIRFLOW, EFFORTLESS COOLING

The LANCOOL 217 INF is equipped with high-performance front and rear fans, plus additional fan mounting options at the top and bottom of the chassis. This flexible airflow setup maximizes heat

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

dissipation and ensures smooth, stable performance for all internal components.

To maximize cooling performance, the front features two large 170 mm fans (30 mm thick) with FDB bearings for low noise and extended lifespan. Compared with previous models, the LANCOOL 217 INF reduces noise by 1 dBA while improving airflow efficiency.

The rear features a 140 mm fan (30 mm thick) that efficiently exhausts heat, maintaining stable airflow and optimal system temperature.

The front fans come with a metal mesh dust filter that prevents dust intake and accidental fan contact. The filter can be easily detached for quick cleaning.

Independently tested by the PPLP Lab, the LANCOOL 217 INF delivers exceptional thermal performance, ranking among the top of its class. Its optimized airflow structure and powerful cooling capacity earned it the PPLP “S-Class” Thermal Performance Rating, proving its superior temperature management.

Flexible Installation Options

The LANCOOL 217 INF includes screws for 120 mm fan installation, allowing users to mount fans on the PSU shroud for additional airflow.
Alternatively, two 120 mm fans can be installed beneath the PSU cover to create more space and improve internal cooling flexibility.

FLEXIBLE DESIGN, VERSATILE LAYOUTS

The PCIe slot bracket can be turned 90 degrees to support vertical GPU mounting. In this setup, the bottom fan can be moved under the PSU shroud for a hidden look, giving users more flexibility when building their system.

DUAL PSU MOUNTING,FLEXIBLE BUILDS

The LANCOOL 217 INF supports two PSU mounting ways, giving the users more options based on the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

PSU size, cable routing, and overall build layout. This flexible design makes it easier to set up the system, enhancing convenience and compatibility.

- Mid-tower chassis engineered for high-volume airflow with a bold infinity-mirror front aesthetic
- Dual 170 mm front fans + 140 mm rear fan deliver strong, efficient system cooling
- Tempered-glass front panel with precision cutouts and integrated infinity-mirror lighting
- Supports wireless fan and ARGB lighting control through L-Connect 3 (L-Wireless controller required), I/O buttons, or motherboard sync
- Compatible with back-connect motherboards for cleaner cable routing and a streamlined build
- Certified PPLP S-Class Thermal Performance for reliable cooling under demanding loads

Summary: Lian Li Lancool 217 INF. Form factor: Midi Tower, Type: PC, Product colour: Black. Front fans installed: 2 x 170 mm, Rear fans installed: 1x 140 mm, Rear fans diameters supported: 120,140 mm. Supported HDD sizes: 3.5,2.5". Width: 238 mm, Depth: 482 mm, Height: 503 mm | Vendor Homepage: https://lian-li.com/product/lancool-217-inf/ | Type: PC | Form factor: Midi Tower | Product colour: Black | Material: Steel/Tempered glass | Supported motherboard form factors: ATX/EATX/micro ATX/Mini-ITX/SSI EEB | Number of 3.5" bays: 1 | Number of 2.5" bays: 2 | Number of expansion slots: 7 | Side window: Yes | Suitable for: Home/Office | Illumination: Yes | Illumination colour: Multi | Illumination location: Front | Tempered glass panel(s): Yes | Anti-dust filter: Yes | Cable management: Yes | On/off button: Yes | RGB control button: Yes | Maximum CPU cooler height: 180 | Maximum graphics card length: 380 | Maximum PSU length: 220 | Power supply included: No | USB 3.0: 2 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | Combo headphone/mic port: Yes | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Front fans installed: 2 x 170 mm | Rear fans installed: 1x 140 mm | Number of rear fans supported (max): 2 | Rear fans diameters supported: 120/140 | Number of top fans supported (max): 3 | Top fans diameters supported: 120/140 | Number of bottom fans supported (max): 3 | Bottom fans diameters supported: 120 | Top radiator sizes supported: 240/280/360 | Supported HDD sizes: 2.5/3.5 | Width: 238 | Depth: 482 | Height: 503 | Unit Calculated Weight: 13.6 | Product Net Weight: 10 | Unit Calculated Volume: 0.1074 | Units per Shipping Box: 1 | Unit Width: 58 | Units per Pallet: 0 | Shipping Box Height: 32.5 | Unit Depth: 57 | Unit Height: 32.5 | Name: CASE MIDITOWER EATX W/O PSU/G99.LAN217INFX.00 LIAN LI | Model name: Lian Li Lancool 217 INF Black (G99.LAN217INFX.00) | Case product features: Transparent panel

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950