

DAP140

v1.0



WRL ACCESS POINT/DAP140 TELTONIKA



Model: DAP140

Manufacturer: TELTONIKA

EAN: 4779051843251

Product Code: 1424877

R1,821 ~~R2,217~~

The DAP140 is a Teltonika industrial wireless access point with passive PoE-in, designed to enhance Wi-Fi coverage and performance in industrial environments. Featuring Wi-Fi 4 with Wi-Fi mesh and Fast Roaming, as well as dual RJ45 ports and support of up to 50 simultaneous connections, this wireless access point is integral in maintaining reliable connectivity. An integrated DIN rail bracket, 3-pin power connector, and industrial-grade aluminium housing make the DAP140 the ideal access point for industrial applications.

- Seamless Wi-Fi 4 with Wi-Fi mesh & Fast Roaming
- 2 x 10/100 RJ45
- 1 x 3-pin power connector tailored for industrial use
- Easy mounting for plug-and-play deployment

Summary: Teltonika DAP140. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: OWE, WPA-EAP, WPA-PSK, WPA2-EAP, WPA2-PSK, WPA3-EAP, WPA3-SAE. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: Black | Vendor Homepage:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

<https://teltonika-networks.com/products/access-points/DAP140/> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | Ethernet LAN data rates: 10/100/1000 | Networking standards: IEEE 802.11b/IEEE 802.11e/IEEE 802.11g/IEEE 802.11k/IEEE 802.11n/IEEE 802.11r/IEEE 802.11s/IEEE 802.11v/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Cabling technology: 10/100Base-T(X) | Fast roaming: Yes | Wireless meshing: Yes | Security algorithms: OWE/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-EAP/WPA-PSK | MAC address filtering: Yes | VPN support: OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard, Tinc, Tailscale | Universal Plug and Play (UPnP): Yes | DHCP server: Yes | DHCP client: Yes | Supported network protocols: TCP, UDP, IPv4, IPv6, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL/TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SNMP, MQTT, Wake On Lan (WOL) | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Web-based management: Yes | Command-line interface (CLI): Yes | Ethernet LAN (RJ-45) ports: 2 | WAN connection: Ethernet (RJ-45) | RS-232 interface: No | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Placement: Shelf, Wall | Product colour: Black | Housing material: Aluminium | International Protection (IP) code: IP30 | Reset button: Yes | LED indicators: Power | Antenna type: External | Antenna connector type: RP-SMA | Built-in processor: Yes | Processor frequency: 580 | Flash memory: 128 | Internal memory: 16 | Operating system installed: RutOS | Width: 113.1 | Depth: 68.6 | Height: 25 | Weight: 150 | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Storage temperature (T-T): 10 - 90 | Storage relative humidity (H-H): -50 - 75 | Unit Calculated Weight: 0.259 | Product Net Weight: 0.1423 | Unit Calculated Volume: 0.0011794 | Units per Shipping Box: 20 | Unit Width: 15 | Shipping Box Height: 17 | Unit Depth: 18 | Unit Height: 3.5 | Name: WRL ACCESS POINT/DAP140 TELTONIKA | Model name: DAP140000000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950