



UPS ERA PLUS DC POE 24VDC/FGCERAPLDC252 TECNOWARE

Model: FGCERAPLDC252

Manufacturer: TECNOWARE

EAN: 8026475177988

Product Code: 1424910

R1,963

UPS ERA PLUS DC 9VDC / 12VDC - POE 24VDC / 48VDC - USB 5VDC TOGETHER ON, 8,800 mAh batteries, It has Black-Out, overvoltage and undervoltage protection. DC technology. Dimensions 16x2,8x10,5cm, weight 0,5 kg. Equipped with On-Off button with integrated multifunction LED for signaling the operating status. Designed to protect devices such as WIFI, Modem / router, VOIP, Cameras and recharge of devices such as Tablet, SmartPhone, Bluetooth headphones, Smartwatch and etc. Totally silent.

- Complete protection from black outs and voltage surges (overvoltages and undervoltages)
- Designed to protect devices such as WIFI, Modem / router, VOIP, Cameras and etc
- Charging of devices such as Tablet, SmartPhone, Bluetooth headphones , Smartwatch and etc
- Equipped with On-Off button with multifunction LED
- Lithium batteries from 8.800 mAh
- POE function to add power on the LAN cable

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Output connections: DC 5.5x2, 5 mm - RJ45 - USB
- Wide compatibility thanks to the 10 Tips included in the package

Summary: Tecnoware FGCERAPLDC252. UPS topology: Standby (Offline), Output power: 18 W, Input operation voltage (min): 110 V. Battery technology: Lithium-Ion (Li-Ion), Battery capacity: 8800 Ah, Typical backup time at full load: 240 min. Product colour: Black, International Protection (IP) code: IP20. Width: 160 mm, Depth: 105 mm, Height: 28 mm. Package width: 170 mm, Package depth: 140 mm, Package height: 35 mm | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/644> | UPS topologija: Budėjimo režimas (neprisijungus) | Išvesties galia: 18 | Įvesties eksploatacinė įtampa (min.): 110 | Įvesties eksploatacinė įtampa (maks.): 240 | Įėjimo dažnis: 50/60 | Išvesties darbinė įtampa (min.): 5 | Įvesties fazių skaičius: 1 | Išvesties fazių skaičius: 1 | Garso lygis: 40 | USB prievadas: Taip | Ethernet LAN (RJ-45) portų kiekis: 1 | Baterijos technologija: Ličio-jonų (Li-Ion) | Baterijos talpa: 8800 | Tipiško laikino maitinimo trukmė pilna apkrova: 240 | Produkto spalva: Juoda | LED indikatoriai: Taip | Tarptautinės apsaugos (IP) kodas: IP20 | Darbo temperatūros diapazonas (TT): 0 - 55 | Darbinis aukštis: 0 - 3000 | Plotis: 160 | Ilgis: 105 | Aukštis: 28 | Svoris: 500 | Pakuotės plotis: 170 | Pakuotės gylis: 140 | Pakuotės aukštis: 35 | Bruto svoris: 0.652 | Neto svoris: 0.5 | Vienetų skaičius vienoje siuntimo dėžėje: 5 | Vieneto plotis: 17 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 22 | Vieneto gylis: 20.5 | Vieneto aukštis: 5.5 | Name: UPS ERA PLUS DC POE 24VDC/FGCERAPLDC252 TECNOWARE | Model: FGCERAPLDC252

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950