

Wireless Device UBIQUITI 1000 Mbit/s 1xLAN ports LOCO5AC

Model: LOCO5AC

Manufacturer: UBIQUITI

EAN: 817882027250

Product Code: 1424926

R1,706

The indoor/outdoor NanoStation® AC and NanoStation AC loco are compact, high-performance CPEs featuring airMAX® AC technology and a dedicated Wi-Fi radio for management.

Sleek Industrial Design

The NanoStation AC and NanoStation AC loco represent the next evolution of the iconic CPE design that revolutionized the Wireless ISP industry.

Dual Ethernet Connectivity

The NanoStation AC provides a secondary Ethernet port with software-enabled PoE. Use this port to conveniently power an external device, such as a PoE security camera, for seamless IP video integration.

Management Wi-Fi Radio

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Each NanoStation AC model integrates a separate Wi-Fi radio for fast and easy setup using your mobile device.

Improved Surge Protection

The NanoStation AC and NanoStation AC loco feature enhanced protection against ESD events.

Now with airOS®8

airOS®8 provides powerful features, including airMAX® ac protocol support, real-time RF analytics, and an all-new design for enhanced usability.

Summary: Ubiquiti NanoStation 5AC Loco. 5 GHz, Maximum data transfer rate: 1000 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: https://www.ubnt.com/airmax/nanostation-ac/ | 5 GHz: Taip | Didžiausias duomenų perdavimo greitis: 1000 | Eterneto LAN duomenų perdavimo norma: 10/100/1000 | Duomenų pralaida: 450 | Dažnių juosta: 5.150 - 5.250, 5.250 - 5.350, 5.470 - 5.725, 5.725 - 5.850 | Moduliacija: 16-QAM/256-QAM/64-QAM/BPSK/QPSK | Didžiausias perdavimo atstumas, kai naudojama lauke: 10000 | Ethernet LAN (RJ-45) portų kiekis: 1 | Maitinimas per Eternetą (PoE): Taip | AC įėjimo įtampa: 24 | Įvesties srovė: 0.5 | Talpinimo: Lubos | Produkto spalva: Balta | LED indikatoriai: Energija/Signalo stiprumas/Tinklas | Antenos tipas: Vidinis | Integruotas procesorius: Taip | Vidinė atmintis: 64 | Numatyta operacinė sistema: AirOS | Sertifikavimas: CE, FCC, IC | Plotis: 179 | Ilgis: 77.5 | Aukštis: 59.1 | Svoris: 180 | Darbo santykinės drėgmės diapazonas: 5 - 95 | Darbo temperatūros diapazonas (TT): -40 - 70 | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 0.4 | Neto svoris: 0.18 | Vienetų skaičius vienoje siuntimo dėžėje: 20 | Vieneto plotis: 6 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 23 | Vieneto gylis: 20 | Vieneto aukštis: 11.5 | Name: WRL CPE OUTDOOR 5GHZ/NANOSTATION LOCO5AC UBIQUITI | Model: UBIQUITI airMAX NanoStation 5AC Loco | Model name: NanoStation 5AC Loco

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950