Dahua Technology CS4010-8ET2GT-60 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue

Model: CS4010-8ET2GT-60

Manufacturer: DAHUA

EAN: 6937552421417

Product Code: 1424983

R1,557

- 8 × RJ-45 10/100 Mbps PoE ports, 2 x RJ-45 Gigabit ports
- 60 W total PoE budget, 802.3af/at on all PoE ports, additional Hi-PoE on orange port

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from –10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLynk App and performs real-time monitoring of the network
- Easy config to auto detect and set up network and security systems

Summary: Dahua Technology CS4010-8ET2GT-60. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 5.6 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3az, IEEE.... DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: https://transmission.dahuasecurity.com/en/product-list/business/cloudmanagementsolution/networkswitch/cs4010-8et2gt-60 | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L2 | Duomenys perduodami į debesies platformą: Taip | Web pagrįstas valdymas: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 10 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | Greito eterneto (varis) prievadų skaičius: 8 | Gigabit Ethernet (varinis) portų kiekis: 2 | Maitinimo jungtis: DC lizdas | Tinklo standartai: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | 10G parama: Ne | Portų mirroring: Taip | Eterneto LAN duomenų perdavimo norma: 10,100,1000 | Srauto kontrolės palaikymas: Taip | Transliacijos audros valdymas: Taip | VLAN palaikymas: Taip | VLANs skaičius: 32 | Perjungimo pajėgumas: 5.6 | Persiuntimo dažnis: 4.17 | Adreso lentelės dydis: 8000 | Jumbo Frames palaikymas: Taip | „Jumbo“ kadrai: 9216 | Paketo buferio atmintis: 4 | DHCP funkcijos: DHCP client | Apsauga nuo nesklandaus ryšio: Taip | IP-MAC prievado sąsaja: Taip | Multicast palaikymas: Taip | Stovo montavimas: Ne | Produkto spalva: Mėlyna | Korpuso medžiaga: Metalas | Atstatymo mygtukas: Taip | LED indikatoriai: Taip | Montuojamas ant sienos: Taip | Vidutinis laikas tarp trikčių (MTBF): 2837361 | Maitinimo šaltinis: DC/PoE | Pridėtas maitinimo šaltinis: Taip | DC įėjimo įtampa: 53 | Įvesties srovė: 1.22 | Maitinimas per Eternetą (PoE): Taip | Maitinimo per Eternetą (PoE) prievadų skaičius: 8 | Bendrosios galios per Eternetą (PoE) charakteriskos: 60 | Darbo temperatūros diapazonas (TT): -10 - 55 | Sandėliavimo temperatūros norma (T-T): -40 - 70 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Plotis: 103.3 | Ilgis: 184.6 | Aukštis: 27 | Svoris: 360 | Pridėti kabeliai: AC | Instrukcija: Taip | Pakuotės plotis: 137 | Pakuotės gylis: 252 | Pakuotės aukštis: 113 | Paketo

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

svoris: 920 | Atitikties sertifikatai: CE | Bruto svoris: 1 | Neto svoris: 0.36 | Vienetų skaičius vienoje siuntimo dėžėje: 20 | Vieneto plotis: 13.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 25 | Vieneto gylis: 25 | Vieneto aukštis: 11 | Name: NET SWITCH 10PORT 8POE 10/100M/CS4010-8ET2GT-60 DAHUA | Model name: CS4010-8ET2GT-60

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950