

Axagon EEM2-SC External USB-C 10Gbps screwless metal box for M.2 NVMe SSD disks. Grey

Model: EEM2-SC

Manufacturer: AXAGON

EAN: 8595247909435

Product Code: 1425305

R902

Aluminum external AXAGON EEM2-SC RIBBED box with USB 10Gbps interface designed for M.2 NVMe SSDs. A stable and fast connection is ensured by a reversible USB-C connector. In the package you will find a USB-C -> USB-C cable to connect the box to your computer.

Thanks to the USB 10Gbps interface, the transmission rate is up to 10 Gb/s. The external M.2 box supports modern features such as UASP, TRIM and enables reading S.M.A.R.T. disk status monitoring information.

The advantage of the box is the attachment of four different lengths of SSD cards - 30, 42, 60 and 80

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

mm. M.2 drives can be single-sided or double-sided. The box does not limit the capacity of inserted SSD.

Screwless opening makes installation and removal of the M.2 SSD drive easier. This makes disk replacement quick and easy, significantly speeding up data migration, testing, cloning, and storage expansion.

The ribbed design and aluminum casing of the box ensure excellent cooling of the inserted M.2 SSD drive. This extends its service life and also prevents the disk from slowing down, so-called „Thermal Throttling“. The outer metal casing is black and prevents unwanted fingerprints.
By inserting the M.2 SSD in the box, you will easily create fast compact and universal external disk. The box can be used with computers and notebooks, as well as with mobile phones and tablets.

Input:
• USB 10Gbps (USB 3.2 Gen 2), connector USB-C female.
• Compatible with USB 5Gbps, USB 20Gbps, USB 40Gbps and Thunderbolt 3/4/5.

Device support:
• NVMe M.2 SSD disks,
• designed for M key or B+M key card formats,
• NGFF 75-pin M key slot for M.2 drives.

Other features:
• Supports transmission rates 10.000 / 5.000 Mbit/s.
• Support for NVMe (PCI Express) M.2 SSD drives without maximum capacity limitations.
• Support of M.2 disks of these sizes – 2230, 2242, 2260 and 2280 mm.
• Support of both one-sided and double-sided M.2 SSDs.
• Compliant with PCI Express Base Specification Revision 3.1a specification.
• Compliant with NVM Express 1.3 specification.
• Compliant with USB Mass Storage Class specification.
• The real box bandwidth / transmission rate is about 1000 MB/s (1 GB/s), it is given by the limits of the USB 3.2 Gen 2 interface.
• Supports BOT (Bulk-Only Transport).
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

• Supports TRIM functionality to limit gradual degradation of the SSD performance over time.
• Supports S.M.A.R.T. (Self-Monitoring, Analysis, and Reporting Technology) system monitoring disk condition.
• SSD boot support in external box.
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Power supply via USB bus up to 900mA from one USB port is sufficient in all cases.
• Blue LEDs indicating connection to the computer's USB port (steady light) and data transfer (flashing).
• Heavy-duty aluminium body and thermal conductive pad helps to better cooling the M.2 SSD disk.
• Higher box surface temperature is not a defect - thanks to the aluminum body, the heat generated by the disk operation is better drained and transferred to the environment.
• Connection via USB 3.2 Gen 2 type C female connector.
• USB type C male / USB type C male cable length 30 cm in the package.

Other data:
• Dimensions: 116 × 39 × 14 mm (W × D × H).
• Weight: 47 g (without cable, without disk)

Supported operating systems:
• Windows 7 / 8.1 / 10 / 11 and later, macOS, iPadOS, iOS, Linux, Chrome OS and Android.
• Compatibility depends on the operating system and device manufacturer support.
• Note: when Windows 7 used it is necessary to check OS support and driver availability with the M.2 SSD manufacturer.

Package contains:
• USB-C 10Gbps external box for M.2 SSD,
• USB-C – USB-C cable 30 cm long,
• 1 pc thermal conductive pad,
• multilingual manual CZ / DE / DK / ENG / ESP / EST / FIN / FR / GR / HR / HU / IT / LT / LV / NL / NOR / PL / PT / RO / SK / SLO / SRB / SWE / TR / UA / ALB / BG / BOS / CN / ARA,
• packed in a cardboard box with hanging hole.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950