



**NETGEAR
GS510TPP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Black**

Model: GS510TPP-100EUS

Manufacturer: NETGEAR

EAN: 606449119015

Product Code: 1436982

R7,738

Smart Managed Switches just got more powerful and flexible

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

As a leading provider of network equipment for SMBs, NETGEAR understands the importance of providing great choice of PoE port counts and power budgets that can adapt to the business's needs, whether in the hospitality, catering, education or retail domains.

The GS510TLP 8-Port Gigabit Smart Managed Switch with PoE+ and 2 SFP Ports joins the NETGEAR Standalone Smart Managed Switches family, adding full 8 port PoE+ support for deployment of modern high-power PoE devices. Cautious spender organizations can now deploy denser PoE+ devices connected to a cost-effective switch, with a reasonable PoE power budget of 75W. Fan-less, the GS510TLP supports perfectly silent desktop operation or rack mounting.

Organizations who buy infrastructure for the long term and want future proofing for the unforeseeable can require GS510TPP 8-Port Gigabit Smart Managed Switch with PoE+ and 2 SFP Ports: 190W PoE budget offers more headroom. Temperature- and load-based fan-speed control combines accurate monitoring with minimized system acoustic noise: unlike other high power PoE switches on the market, the GS510TPP supports quiet desktop operation or rack mounting with a maximum of 32dB at full power and 25°C (77°F) ambient.

The GS418TPP Easy Mount 16-Port Gigabit Smart Managed Switch with PoE+ and 2 SFP Ports is future-proof with 240W of PoE budget and ideal for "Virtually Anywhere deployments. Slim design (3.94 inches, 10 cm deep) and mounting accessories allow for access point, IP camera or VoIP endpoint placement optimization and cabling efficiency even outside the rack. The GS418TPP supports Easy Mount quiet operation or rack mounting with a maximum of 33dB at full power and 25°C (77°F) ambient