



CLUB3D

Thunderbolt™ 4

Certified 12-in-1

Docking Station



Model: CSV-1582

Manufacturer: CLUB3D

EAN: 8719214472955

Product Code: 1449112



CSV-1582

R5,263

Features:

- Adopting Goshen Ridge solution
- Combining the TB4 features with the ease of an integrated dock, allowing you to output 3 Streams to 3 displays simultaneously with extended desktop displays on a TB4/USB4 Windows PC.
- Slim compact aluminum design
- Thunderbolt™ 4 Certified
- Designed for Thunderbolt™ 4 based PCs and Thunderbolt™ 3/DP-Alt-mode based PC's and Macs™ utilizing MacOS™ 11 and later versions (Limitations can vary on different Apple proprietary Silicon).
- Support Thunderbolt™ 4 max. 40Gbps for high speed data and outstanding video transfer, downward compatible with TB3, USB4, DP™ Alt mode, USB protocol
- Allow to output single 8K30Hz, dual 4K/60Hz or triple (4K/60Hz*3) displays with extended desktop displays on Windows based systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- RJ45 supports 10M/100M/1000M/2.5G bandwidth
- 1x Thunderbolt™ 4 downstream port, allow you to cascade Thunderbolt™ devices
- Self-powered from DC power adapter with max 96W for host, max 134W for host and Dock
- Support smart power which enables to flexibly distribute power to PC and Hub in real time according to the consumption of connected devices
- Support TB4/USB4/TB3/DP-Alt-mode Hosts
- Supports both the Kensington Anti-theft lock as well as the standard Nano Anti-theft lock(which uses Only 70% of the physical space)

Available Interfaces

- Please update your TV Firmware to the version which supports these resolutions/refresh rates !

Upstream: 1x

- Support Thunderbolt™ 4 up to 40Gbps, compatible with Thunderbolt™ 3, USB4, DP Alt mode, USB protocol
- Support TB4/USB4/TB3/DP-Alt-mode Hosts
- Support max. 96Watt Host charging, 5V/9V/15V@3A,20V@4.8A

Downstream:

Stream 1:

- 1x Support Thunderbolt™ 4 up to 40Gbps, compatible with Thunderbolt™ 4, Thunderbolt™ 3, USB4, DP Alt mode, USB protocol
- Allow you to cascade Thunderbolt™ devices
- Support max 8K30Hz or dual 4K60Hz video
- Thunderbolt™ 4 port supports 15W downstream charging for connected device(The port does not support PD charging)

Stream 2 □ DisplayPort™ :

- Support max 8K/30Hz
- Support DP1.4 Specification
- Support DPCP
- Support RGB, YCbCr444, YCbCr422, YCbCr420
- Support 8/10/12 bit deep color
- Support HDR

HDMI1(Close to DP) □

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Support max 8K/30Hz
- Support HDCP 1.4&2.2
- Support RGB, YCbCr444, YCbCr422, YCbCr420
- Support 8/10/12 bit deep color
- Support HDR

Stream 3 □ HDMI™ 2(Close to USB2.0)

- Support max 4K/60Hz
- Support HDCP 1.4&2.2
- Support RGB, YCbCr444, YCbCr422, YCbCr420
- Support 8/10/12 bit deep color
- Support HDR
- Among all streams, max output 2 streams simultaneously, support output dual 4K/60Hz (or 8K/30Hz+4K/30Hz) or triple(4K/60Hz*3) displays with extended desktop displays on Windows system
- DP™ and HDMI™ 1 Port output the same pictures on Mac OS system

Note□

The actual resolution supported is determined by the host and the Display together.

Other Connections :

1x USB3.2 Gen2 Type-C

- Compliant with USB3.2 Gen 2 with max 10Gbps data transmission, downward compatible with lower versions
- Support max 5V/1.5A downstream charging
- Support short-circuit, over-current protection
- Support reversible connection

2x USB3.2 Type-A Gen2 (close to USB-C 10G)

- Compliant with USB3.2 Gen 2 with max 10Gbps data transmission, downward compatible with lower versions
- Support max 900mA downstream charging per port
- Support short-circuit, over-current protection

2x USB2.0 Gen1 Type-A(close to RJ45)

- Support max 480Mbps data transmission
- Max 500mA downstream charging per port
- Support short-circuit, over-current protection

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

1x Ethernet RJ45

- Support Gigabit Ethernet, 10M/100M/1000M/2.5Gbps
- Support Wake-On-LAN and Wake-On-WAN
- Light indicator indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data.

1x Audio JACK 3.5mm

- Support 24/32-bit, 44.1/48/96/192/384KHz Sample Rate
- Support Stereo output and microphone input
- Automatic detection switch to CTIA/MTP mode

1x DC Power Jack

- Support smart charging, dynamically distribute power to PC and Hub according to the requirement of the connected devices
- Used to connect 21V 134W DC power supply
- Max 124W power for host and the DOCK and 10W is for buffer power
- Max 96W for host charging
- Supports both the Kensington Anti-theft lock as well as the standard Nano Anti-theft lock (which uses Only 70% of the physical space)

OS Support:

- Windows 10 or upwards, Mac 13.5.2 (Limitations can vary on different Apple proprietary Silicon)