



InLine DisplayPort 2.1 AOC cable, UHBR, black 20m



Model: 17220A

Manufacturer: INLINE

EAN: 4043718331611

Product Code: 1449231

R2,357

Future-proof technology: Supports the latest DisplayPort 2.1 standard for highest data rates and full compatibility with modern systems.

Lossless transmission: The active optical cable solution (AOC) enables interference-free signal transmission over up to 3 meters.

Maximum picture quality: Supports resolutions up to 10K @ 60 Hz with DSC, 8K @ 60 Hz or 4K @ 144 Hz - ideal for graphics-intensive applications.

Rugged and durable: Aramid-protected TPU cable with metal connectors and gold-plated contacts for durable use.

Easy integration: Plug & play functionality enables fast, error-free installation in professional system environments.

The InLine® DisplayPort 2.1 AOC cable was developed for professional requirements in IT

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

environments where the highest signal quality and reliability are required. The combination of active optical technology and high-quality workmanship enables data transfer rates of up to 54 Gb/s - ideal for graphics-intensive applications such as CAD, multimedia productions or high-end presentation systems.

The hybrid cable combines four optical fibers and seven copper wires for an optimal balance between range and performance. Thanks to the directional design with robust metal connectors, a secure and stable connection is possible. The cable supports current standards such as HDCP2.2, EDID and DPCP and is fully backwards compatible with DisplayPort 1.4 and 1.2.

The black TPU sheathing with aramid-reinforced inner structure effectively protects the cable from wear and tear and mechanical stress. Installation is straightforward via Plug & Play, without additional configuration. Ideal for use in conference rooms, control centers, industrial facilities or IT infrastructures.

Hybrid cable with 4 optical fibers & 7 copper strands

Cable diameter: Ø 4.8 mm, aramid-reinforced

Gold-plated DisplayPort metal connectors

Max. Data rate: 54 Gb/s (UHBR 13.5)

Supports: 3D, HDCP2.2, DPCP1.0, EDID

DisplayPort version: 2.1, backwards compatible with DP 1.4 / 1.2

Maximum resolutions: 10K @ 60Hz (DSC), 8K @ 60Hz (4:4:4 8-bit), 4K @ 144Hz

Plug & Play: no driver installation required

Color: black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950