



Lindy 38360 InfiniBand/fibre optic cable 100 m MPO Multicolour

Model: 38360

Manufacturer: LINDY

EAN: 4002888383608

Product Code: 1450071

R13,343

The Lindy MPO Fibre Optic HDMI® 8K60 Extender is an effective, reliable solution for extending UHD HDMI® transmissions over distances up to 100m using one Type A MPO OM3 multimode fibre optic cable.

The extender can transmit 7680x4320@60Hz 4:4:4 10bit signals up to 100m with a MPO cable with no compression, allowing for distribution of lossless UltraHD content. With HDR (High Dynamic Range), HLG and Dolby Vision support, content can be seen enhanced contrast, and a much wider colour gamut and the support for lossless audio formats including Dolby Atmos & Dolby TrueHD adds powerful multi-channel sound to video content, provide an enhanced experience and sense of realism to the viewer.

The use of MPO multi-mode fibre optic cabling allows for the transmission of high bandwidth data

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

over long distances. Fibre optic cables are also completely immune to any electromagnetic and radio frequency interference which makes this extender an ideal solution for installations within environments susceptible to high interference such as medical, aerospace and manufacturing facilities. The compact size and flexibility also allow for easy installation under floors and within wall partitions.

The low power requirement and super slim form factor provide invaluable flexibility when incorporating this extender into new and existing installations. Both units have integrated fibre optic cables with MPO Male connectors, a Type A MPO Female to Female cable (not included) can be connected to the units using two included MPO couplers.

Both units also have integrated USB cables to provide power, the transmitter unit can be powered by the HDMI® source while the receiver needs to be powered via USB port connecting it to a 5V USB charger or any powered USB port.