



LevelOne 5-Port Fast Ethernet PoE Switch, 802.3at/af PoE, 4 PoE Outputs, 65W



Model: FEP-0511

Manufacturer: LEVELONE

EAN: 4015867195840

Product Code: 1453279

R3,811

The FEP-0511 is a 5-port 10M/100M Fast Ethernet Switch with one uplink port plus 4 ports of Power over Ethernet capability. Per PoE port is power supply up to 30W. The total PoE power budget is 65W. It is an ideal solution where office and home users utilize a combination of PoE and non-PoE enabled devices.

Four ports on the FEP-0511 are PoE enabled making it an ideal solution for most office users that have PoE enabled devices located around the office. These products can include a mixture of PoE IP Phones, PoE wifi APs and PoE IP Cam. It is the perfect answer for offices that are upgrading their office equipment and LAN infrastructure to include PoE capability. The switch automatically detects IEEE 802.3at/af compliant device connected and provides power and data over a single cable to these devices.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The FEP-0511 enables users to deploy a stable and reliable high-speed LAN environment, with store-and-forward switching architecture, packet error filtering and non-blocking packet forwarding. The 802.3x and backpressure flow control mechanisms work respectively for full and half duplex modes. This device supports N-way auto-negotiation protocol that automatically detects networking speed and duplex modes.

For instant error detection, the FEP-0511 is equipped with a full range of LEDs to help monitor and troubleshoot problems on the network.

Key Features

- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- Auto-detection and protection of non-standard PoE devices
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Internal power supply