

ACT AK4172 DisplayPort cable 20 m Black



Model: AK4172

Manufacturer: ACT

EAN: 8716065557190

Product Code: 1476226

R3,983

The ACT AOC 8K DisplayPort 2.1 DP40 UHBR10 cable is made of copper and fiber to connect different devices over long distances up to 100 meters without the loss of data. The Active Optical Cable has a bandwidth of 40Gbps 4:4:4 to handle the resolution of 7680x4320 (8K) @ 60Hz. Additionally, the cable supports: HDR, HDCP 2.2, EDID, Multi-channel audio, Dolby True HD and DTS-HD Master Audio.

AOC: copper and glass for longer distances and the best video and audio quality

The AOC (Active Optical Cable) cable is made of copper and fiber for transferring 8K @ 60Hz over long distances up to 100m without data loss. It has a bandwidth of 40Gbps 4:4:4, also called UHBR10 DP 40.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The cable has a Kevlar protected fiber, an aluminium foiled shielding and is suitable for sensitive applications due to low RFI/EMI. The cable is supplied in a box.

No additional power is needed. The cable supports 3.3V over the full length.

Resolution of 8K @ 60Hz

This 8K DisplayPort cable supports a resolution of 7680x4320 @ 60Hz. Furthermore, the cable supports High Dynamic Range (HDR) video for expansive contrast ratio and color accuracy, HDCP 2.2, EDID, Multi-channel audio, Dolby True HD, and DTS-HD Master Audio.

LSZH

The cable has a LSZH (Low Smoke Zero Halogen) cable jacket that reduces the risk of high concentrations of toxic gases in case the cable is damaged due to fire or short circuit.

Additional features

It is important that the cable is connected correctly. The ACT AOC DisplayPort 2.1 cable is marked to ensure easy identification of the source and display connector. The snap-in connector ensures a reliable connection without the risk of accidental disconnection.

User scenarios

Medical applications: High-resolution imaging is critical in radiology for detailed diagnosis. The 8K DisplayPort 2.1 DP40 UHBR10 cable is used to connect imaging equipment to large displays. The low RFI/EMI minimizes interference with sensitive medical devices.

Nautical applications: The vessel's bridge uses high-definition displays for navigation, radar, and other critical systems. Facilitates connections between equipment located in different parts of the vessel without signal loss. The Kevlar protected fiber offers durability and reliability in harsh marine environments.

Data center applications: Data centers require high-resolution displays for monitoring system performance and security. The LSZH jacket ensures safety by reducing toxic gas emissions in case of

a fire.

Educational applications in lecture halls and auditoriums: Provides clear and detailed visuals for large audiences. Long Distance Capability: Enables connection from the control room to displays across large spaces.

Corporate applications in meeting rooms and conference centers: Executive meeting rooms and conference centers require high-definition displays for video conferencing, presentations, and collaborative work.