



InLine patch cable connector Cat.6A, waterproof IP68, f. industrial application

Model: 699990U

Manufacturer: INLINE

EAN: 4043718291649

Product Code: 1479777

R857

IP68-rated for outdoor use: Reliable network connection in humid, dusty, and extreme temperature conditions.

Sturdy housing for harsh environments: UV-resistant material withstands industrial and weather conditions over the long term.

Flexible compatibility: Supports standard RJ45 patch cables with a cable diameter of 3 to 8 mm – ideal for individual installations.

Up to 10Gb/s transmission: Cat.6A coupling for high network loads and future-proof applications.

Easy installation with M25 thread: Quick, tool-free, and secure – saves time in daily use.

The InLine® Cat.6A patch cable connector has been specially developed for professional outdoor applications. With protection class IP68, it is suitable for environments where moisture, dust, and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

extreme temperature fluctuations are commonplace.

Thanks to its robust, UV-resistant housing, the connector can withstand long-term environmental exposure – from construction sites and industrial installations to telecommunications technology.

The M25 screw connections enable simple, tool-free installation and ensure a secure seal.

The connector supports standard RJ45 patch cables with a cable diameter of 3 to 8 mm and delivers transfer rates of up to 10Gb/s. A 1:1 assignment enables a direct, loss-free connection. This makes it particularly suitable for data-intensive applications where stability and reliability are crucial.

Whether in the machine hall, in the control cabinet, or outdoors, this coupling delivers reliable performance with maximum durability.

Contact resistance: < 10 mOhm

Connection type: 1:1