

Lindy Control Keypad, 6 Keys and Dial - Programmable AV & Room Control Interface



Model: 32306

Manufacturer: LINDY

EAN: 4002888323062

Product Code: 1492443

R4,968

Flexible AV Room Control for Professional Installations

The Lindy Control Keypad with 6 keys and dial provides a programmable and intuitive AV room control solution for meeting rooms, classrooms, lecture theatres and presentation spaces, enabling simple management of multiple connected devices from a single wall-mounted interface.

Programmable Multi-Device AV Control

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Designed for flexible room automation and AV control, this keypad combines six programmable backlit buttons with a rotary dial and integrated control interfaces including LAN, RS-232, RS-485, IR, relay and I/O ports. Simple configuration through Lindy Pro Control software allows integrators to create customised room control systems for professional AV environments while PoE support simplifies installation and deployment.

At a Glance

6 programmable backlit keys

Provides fast and intuitive control of room functions and connected AV devices.

Integrated rotary dial

Enables precise volume adjustment and additional programmable control functions.

Comprehensive connectivity

Supports LAN, RS-232, RS-485, IR, relay and I/O device control.

PoE or external power

Flexible powering options reduce installation complexity and cabling requirements.

Centralised room control

Provides a simple and professional user interface for managing displays, switchers, audio systems, lighting, screens and other room devices from a single wall-mounted controller.

Flexible integration across AV systems

Integrated LAN, RS-232, RS-485, IR, relay and I/O interfaces support control of a wide range of professional AV and automation devices within modern meeting and presentation spaces.

Customisable operation and workflows

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The programmable buttons and rotary dial can be configured through Lindy Pro Control software to create tailored room control experiences for specific environments and operational requirements.

Simplified installation with PoE support

Power over Ethernet support enables power and network connectivity over a single cable, reducing installation time and improving deployment flexibility in professional AV installations.

Professional wall-mounted design

The compact and durable design integrates neatly into meeting rooms, classrooms and corporate environments while maintaining reliable long-term operation.

Suitable for scalable AV environments

Designed for integration within larger room control and automation systems, making it suitable for both standalone deployments and enterprise-wide AV control infrastructures.

Typical Applications

The Control Keypad with 6 keys and dial is ideal for conference rooms, boardrooms, classrooms, lecture theatres, hospitality spaces and presentation environments requiring intuitive control of displays, audio systems, lighting, screens and room automation devices. It is particularly suited to professional AV installations where customised room control and simplified user interaction are essential.

Technical Summary

The keypad features an ARM Cortex-A7 processor running Linux with integrated 100Mbps network support via an RJ45 PoE connection. Control interfaces include four RS-232 ports, one RS-485 port, two IR outputs, relay outputs and two configurable I/O ports for flexible integration with professional AV and automation systems.

The programmable interface includes six backlit buttons with custom-labelled caps and a rotary dial with push-button functionality and status LEDs. Configuration and programming are managed

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

through Lindy Pro Control software for customised room control deployment.

The compact metal enclosure measures 86 x 86 x 52.7mm and supports both PoE and external 5VDC powering. The keypad is supplied with Phoenix connectors, mounting screws, a multi-country power supply and quick installation documentation, and is backed by a 2-year warranty.