



InLine 17991C cable gender changer HDMI A Mini HDMI C Black, Grey

Model: 17991C

Manufacturer: INLINE

EAN: 4043718338207

Product Code: 1506360

R830

Direct signal routing:The 1:1 pin assignment enables unaltered transmission of digital audio and video signals without conversion.

Suitable for high-resolution applications:Supports UHD 8K and has been successfully tested in practice with 3840x2160 at 120 Hz and 4:4:4 8 bits.

Reliable contact technology:Gold-plated contacts reduce contact resistance and support stable signal paths.

Robust aluminum housing:The high-quality metal construction protects the internal components and is suitable for demanding environments.

Flexible integration:Ideal for connecting or extending existing HDMI routes between mini HDMI sources and HDMI infrastructures.

The HDMI adapter reliably connects mini HDMI sources to an existing HDMI signal path. The HDMI A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

socket and mini HDMI C plug enable direct and uncomplicated integration without the need for additional active components. The 1:1 pin assignment ensures unadulterated transmission of digital audio and video signals, thereby supporting stable transmission paths.

The adapter is suitable for resolutions up to UHD 8K and has been successfully tested with 3840x2160 at 120 Hz and 4:4:4 8 bits. This makes it suitable for applications that require high image quality and reliable signal transmission. The gold-plated contacts minimize contact resistance and contribute to a permanently stable connection.

The robust aluminum housing protects the contact surfaces and allows use in both stationary and mobile setups. The recommended total length of the signal path is up to 1.5 meters and can reach a maximum of 2 meters.

With its compact design, the adapter offers a reliable solution for professional applications where mini HDMI signals need to be securely integrated into HDMI-based systems.

Item width: 1.9 cm

Item height: 1.0 cm

Item length: 3.6 cm

Audio: Yes

Housing material: Aluminum

Outer jacket: Black PVC

Side A: HDMI A socket

Side B: Mini HDMI C plug

Signal type: Audio/video

Type: Gold-plated contacts

Contact resistance: 3 ohms

Insulation resistance: DC 300V 10M ohms

Operating temperature: -10 °C to +60 °C

Storage temperature: -20 °C to +80 °C

Recommended total length: up to 1.5 m, maximum 2 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950