



InLine Serial extension, 9pin male / female, moulded, 1:1 assigned, 15m

Model: 12211

Manufacturer: INLINE

EAN: 4043718002672

Product Code: 1516671

R966

Reliable serial signal extension:The extension enables stable expansion of existing RS232, RS422 or RS485 connections between system components with a 9-pin Sub-D interface.

1:1 assigned for direct signal transmission:All pins are connected one-to-one and enable unaltered transmission without cross-wiring.

9-pin Sub-D plug to socket:The assembly with 9-pin plug and 9-pin socket allows easy extension of existing DB9 connections.

Moulded connector design:The moulded connectors support a mechanically stable connection and increase resistance in daily use.

Flexible length options:Available in 2 metres, 3 metres, 5 metres, 7 metres, 10 metres, 15 metres and 20 metres for installations tailored to your needs.

The InLine® serial extension with 9-pin Sub-D plug to 9-pin Sub-D socket is used to extend existing

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

serial interfaces. It is suitable for RS232, RS422 and RS485 connections between peripheral devices, data switches and PC or server systems.

Thanks to the 1:1 pin assignment, all pins are directly connected. There is no cross-wiring. This means that the signal structure of the existing connection remains unchanged.

The moulded connectors support a stable mechanical connection and are designed for regular use.

The standardised 9-pin Sub D assembly allows for easy integration into existing installations.

The cable is available in several defined lengths and can be flexibly adapted to different installation requirements.

Connector type: 9-pin Sub-D plug to 9-pin Sub-D socket

Assignment: 1:1

Supported interfaces: RS232, RS422, RS485

Design: moulded connectors