Asrock H810M-H Intel H810 LGA 1851 (Socket V1) micro ATX

Model: H810M-H

Manufacturer: ASROCK

EAN: 4711581490833

Product Code: 1546376

R2,133

Certification: FCC, CE, ErP/EuP ready | Supported memory clock speed (max): 6400 MHz | PCI Express x16 (Gen 4.x) slots: 1 | HDCP version: 2.3 | PCI Express x1 (Gen 4.x) slots: 1 | BIOS type: UEFI AMI | Audio chip: Realtek ALC897 | TPM connector: Yes | CPU fan connector: Yes | Product colour: Black | Supported storage drive interfaces: M.2, SATA III | Processor manufacturer: Intel | Unbuffered memory: Yes | Processor socket: LGA 1851 (Socket V1) | Wi-Fi: No | USB 2.0 connectors: 2 | Ethernet LAN (RJ-45) ports: 1 | Maximum resolution: 3840 x 2160 pixels | Screws included: Yes | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | Motherboard chipset family: Intel | HDMI version: 2.1 | Motherboard chipset: Intel H810 | Number of SATA III connectors: 4 | Depth: 193 mm | Ethernet interface type: Gigabit Ethernet | High Dynamic Range (HDR) supported: Yes | USB 2.0 ports quantity: 4 | HDCP: Yes | Number of storage drives supported: 5 | Compatible processor series: Intel Core Ultra (Series 2) | LAN controller: Realtek RTL8111H | Ethernet LAN: Yes | Number of memory slots: 2 | Supported memory types: DDR5-SDRAM | Memory slots type: DIMM | Motherboard form factor: micro ATX | Line-in: Yes | Audio output channels: 7.1 channels | Memory channels: Dual-channel | Front panel audio connector: Yes | Windows operating systems supported: Windows 11 x64

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

| PS/2 ports quantity: 1 | Supported storage drive types: HDD & SSD | Cables included: SATA | Microphone in: Yes | Maximum internal memory: 128 GB | 12V power connector: Yes | Supported processor sockets: LGA 1851 | Number of chassis fan connectors: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Number of M.2 (M) slots: 1 | HDMI ports quantity: 1 | ATX Power connector (24-pin): Yes | RGB LED pin header: Yes | Width: 220 mm | Number of CPU fan connectors: 1 | Number of RGB LED pin headers: 1 | 1st M.2 largest key size: 2280 | ECC compatibility: ECC & Non-ECC | 1st M.2 highest PCI Express generation: 4.0

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950