

Motherboard - ASRock X870E Taichi Lite

Model: X870E Taichi Lite

Manufacturer: ASROCK

EAN: 4710483947445

Product Code: 1546377

R8,684

Processor manufacturer: AMD | Ethernet LAN: Yes | USB 3.2 Gen 2x2 Type-C ports quantity: 2 | Depth: 267 mm | Operating system architecture: 64-bit | Wi-Fi: Yes | Compatible processor series: AMD Ryzen™ 8000 Series | RGB LED pin header: Yes | Memory channels: Dual-channel | Width: 305 mm | USB 3.2 Gen 2 (3.1 Gen 2) connectors: 1 | Compatible processor series: AMD Ryzen™ 7000 Series | Bluetooth version: 5.4 | Compatible processor series: AMD Ryzen™ 9000 Series | Ethernet interface type: 5 Gigabit Ethernet | Line-out: Yes | Supported memory clock speed (max): 8200+ MHz | Number of memory slots: 4 | Microphone in: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Supported memory types: DDR5-SDRAM | Memory slots type: DIMM | Wi-Fi standards: Wi-Fi 6E (802.11ax) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 7 (802.11be) | Wi-Fi standards: 802.11b | Maximum number of SMP processors: 1 | Processor socket: Socket AM5 | PCI Express x16 (Gen 5.x) slots: 2 | Wi-Fi standards: 802.11a | Number of USB 2.0 Type-A ports: 2 | Number of Wi-Fi antenna ports: 2 | Motherboard chipset: AMD X870E | Audio output channels: 5.1 channels | Front panel audio connector: Yes | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows 11 x64 | CPU fan connector: Yes | Motherboard chipset family: AMD | Clear CMOS button: Yes | HDMI ports quantity: 1 | Audio chip:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Realtek ALC4082 | Maximum internal memory: 256 GB | S/PDIF out port: Yes | Bluetooth: Yes | Supported storage drive interfaces: Blazing M.2 (PCIe Gen5 x4), Hyper M.2 (PCIe Gen4 x4) | BIOS type: UEFI AMI | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | ATX Power connector (24-pin): Yes | Number of SATA III connectors: 4 | Ethernet LAN (RJ-45) ports: 1 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 5 | LAN controller: Realtek RTL8126 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Motherboard form factor: Extended ATX | Unbuffered memory: Yes | USB 2.0 connectors: 2

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950