



Optoma X309ST
data projector
Desktop
projector 3700
ANSI lumens
DLP XGA
(1024x768) 3D
White

Model: E9PD7DQ01EZ1

Manufacturer: OPTOMA

EAN: 5055387664975

Product Code: 1548201

R9,262

PC in (D-Sub): Yes | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Indonesian | On Screen Display (OSD) languages: Japanese | On Screen Display (OSD) languages: Turkish | On Screen Display (OSD) languages: Spanish | Lamp power: 203 W | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: Norwegian | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Romanian | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Farsi | Offset: 115% | Throw ratio: 0.617:1 | On Screen Display

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(OSD) languages: Arabic | On Screen Display (OSD) languages: Portuguese | Supported 3D formats: Side by side | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Supported 3D formats: Frame packing | Number of OSD languages: 25 | On Screen Display (OSD) languages: Vietnamese | Supported 3D formats: Top and bottom | Number of built-in speakers: 1 | Analog signal format system: NTSC J | Analog signal format system: PAL 4.43 | PC Audio in: Yes | Lamps quantity: 1 lamp(s) | Password protection: Yes | Supported aspect ratios: 4:3 | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | Analog signal format system: SECAM K1 | Service life of light source: 6000 h | Remote control included: Yes | Service life of light source (economic mode): 10000 h | Built-in speaker(s): Yes | Projection distance: 0.4 - 3.1 m | Projector brightness: 3700 ANSI lumens | Projector native resolution: XGA (1024x768) | Composite video in: 1 | Ceiling mounting supported: Y | Light source type: Lamp | Supported aspect ratios: 16:9 | Analog signal format system: SECAM 4.25/4.4 | RMS rated power: 10 W | HDMI connector type: Full-size | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Danish | Serial interface type: RS-232 | Fixed focal length: 7.15 mm | Analog signal format system: SECAM L | PC Audio out: Yes | On Screen Display (OSD) languages: Greek | Market positioning: Presentation | Keystone correction, vertical: - 40 - 40° | Contrast ratio (typical): 25000:1 | AC (power) in: Yes | Projection technology: DLP | Screen size compatibility: 810.3 - 6281.4 mm (31.9 - 247.3") | Power consumption (standby): 0.5 W | Uniformity: 75% | Smart TV: No | Warnings: Avoid placing the projector in high humidity areas to prevent damage to the unit. | Warnings: Be careful when replacing the projector lamp as it can be very hot. | Warnings: Do not look directly into the lens of the projector during operation to avoid damage to your eyes. | AC input frequency: 50/60 Hz | Supported video modes: 576i | Supported graphics resolutions: 1280 x 768 (WXGA) | Supported graphics resolutions: 640 x 480 (VGA) | USB 2.0 ports quantity: 1 | Analog signal format system: SECAM K | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions: 1024 x 768 (XGA) | HDMI ports quantity: 1 | Supported video modes: 480i | Card reader integrated: No | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported video modes: 720p | Analog signal format system: SECAM D | Power source: AC | Product type: Desktop projector | Analog signal format system: NTSC | Analog signal format system: NTSC 3.58 | Horizontal scan range: 15.38 - 91.15 kHz | Analog signal format system: SECAM G | Noise level: 26 dB | Wi-Fi: No | Power consumption (max): 225 W | DVI port: No | Product colour: White | Supported video modes: 480p | Supported video modes: 1080p | Batteries included: Yes | Supported video modes: 1080i | Analog signal format system: NTSC M | Analog signal format system: PAL M | Analog signal format system: PAL | Analog signal format system: SECAM | Native aspect ratio: 4:3 | Analog signal format system:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

PAL D | Analog signal format system: SECAM B | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Width: 316 mm | AC input voltage: 100 - 240 V | Quantity per pack: 1 pc(s) | Analog signal format system: PAL B | Analog signal format system: PAL G | Supported video modes: 576p | Cables included: AC | Height: 108 mm | Ethernet LAN: No | Manual: Yes | Weight: 3 kg | Cable lock slot type: Kensington | Analog signal format system: NTSC 4.43 | Cable lock slot: Yes | On Screen Display (OSD): Yes | Vertical scan range: 50 - 85 Hz | VGA (D-Sub) ports quantity: 2 | Full HD: No | Built-in display: No | 3D: Yes | Analog signal format system: PAL H | Analog signal format system: PAL N | HDMI version: 1.4a | Supported graphics resolutions: 1280 x 800 (WXGA) | Depth: 244 mm | Power consumption (typical): 187 W | Analog signal format system: PAL I

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950