InLine 69927U cable accessory Cable coupler

Model: 69927U

Manufacturer: INLINE

EAN: 4043718346882

Product Code: 1551776

R931

T-distributor for power connections: Triple connection option for 3-core cables – ideal for power distribution in damp rooms and outdoor areas.
Waterproof and robust:IP68-certified, silicone seal and impact-resistant nylon housing for reliable protection against water, dust, and mechanical influences.
Flexible for many applications: Suitable for cable diameters of 4–14 mm, for wire cross-sections of 0.5–6 mm², up to 500 V and 24 A.
Tool-free installation: Simple screw system with secure closure – saves time and ensures a permanent connection.
Ideal for outdoor installations: Suitable for garden lights, pond pumps, workshop cabling, or power distribution in the event sector.

The InLine T-shaped power cable coupler with 3-way design offers a secure and flexible way to distribute electrical power connections – ideal for indoor and outdoor applications. Thanks to its IP68 protection class, the connection is permanently waterproof and provides reliable protection against dust and moisture.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

This 3-pole coupler is specially designed for 3-core power cables. It supports a voltage range up to 230 V and a current rating up to 24 A. The T-distributor is therefore particularly suitable for applications where multiple power outlets are required – e.g., for lighting systems in gardens, on construction sites, or for temporary event installations.
The housing is made of durable nylon (PA66), and the copper contacts ensure reliable electrical conductivity. Installation is carried out using a tool-free screw system: insert the cable, connect it, tighten the caps – done. The integrated silicone seals ensure a secure fit and complete sheathing. The coupling is suitable for cable diameters from 4 to 14 mm and cable cross-sections from 0.5 to 6 mm². With its M20 thread and compact T-shape, it offers maximum flexibility in power distribution – robust, durable, and ready for immediate use.

Material: Nylon (PA66)
Thread size: M20
Contact material: Copper
Seal: Silicone
Temperature range: -40 °C to +105 °C
IP protection rating: IP68
Cable diameter: 4–14 mm
Conductor cross-section: 0.5–6 mm²
Design: 3-way
Number of poles: 3-pole
Rated voltage: 500 V
Rated current: 24 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950