



InLine 69927V cable accessory Cable coupler



Model: 69927V

Manufacturer: INLINE

EAN: 4043718346899

Product Code: 1551777

R946

Cross distributor for power connections: Quadruple connection for 3-core cables – ideal for structured power distribution outdoors or in damp rooms.

Permanently waterproof: IP68-certified, silicone seal and sturdy nylon housing protect against water, dust, and mechanical stress.

Flexible use: Suitable for cable diameters of 4–14 mm and cable cross-sections of 0.5–6 mm² – rated for up to 500 V and 24 A.

Tool-free installation: Quick screw system with secure hold – ensures a tight, mechanically stable connection without tools.

Ideal for complex installations: Perfect for garden systems, pond pumps, LED systems, or power grids with multiple branches.

The InLine power cable coupler with 4-way cross distribution is the perfect solution for complex power distribution – whether in private gardens, on construction sites, or in industrial installations. With four separate connection directions for 3-core cables, this coupler is ideal for branched power networks.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The 3-pole connection supports voltages up to 500 V and currents up to 24 A. Thanks to its robust nylon housing (PA66), high-quality copper contacts, and reliable silicone seal, it offers maximum safety and durability – even in adverse weather conditions. The IP68 protection rating ensures permanently tight and weatherproof connections.

Installation is tool-free thanks to the practical screw cap system. Simply insert the cable, connect it, insert the seal, and tighten the caps – the connection is then mechanically secured and waterproof. The coupling is suitable for cable diameters from 4 to 14 mm and cable cross-sections from 0.5 to 6 mm².

Typical areas of application include garden and outdoor lighting, pond installations, power distribution in workshops, events, or machine parks. The cross shape allows multiple consumers to be supplied with power in a clear and safe manner – ideal for demanding applications.

Material: Nylon (PA66)

Thread size: M20

Contact material: Copper

Seal: Silicone

Temperature range: -40 °C to +105 °C

IP protection rating: IP68

Cable diameter: 4–14 mm

Conductor cross-section: 0.5–6 mm²

Design: 4-way

Number of poles: 3-pole

Rated voltage: 500 V

Rated current: 24 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950