

InLine FireWire 400 1394 Cable 6 to 4 Pin male 1.8m



Model: 34642

Manufacturer: INLINE

EAN: 4043718004133

Product Code: 1551960

R851

FireWire cable IEEE1394 4-pin to 6-pin for stable DV and audio-video transmission

Reliable connection for FireWire devices: Enables stable data transmission between compatible IEEE1394 devices without signal conversion

Direct 4-pin to 6-pin connection: Specifically connects devices with different FireWire connectors without the need for an additional adapter

Suitable for DV and AV applications: Supports continuous data transfer for video and audio devices at up to 400 Mb/s

Clear interface function without misinterpretation: Exclusively for connecting FireWire devices; not for use as an adapter or for other connections

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

This FireWire cable, compliant with the IEEE 1394a standard, is designed for the direct connection of devices with 4-pin and 6-pin FireWire ports. It is suitable for applications requiring stable and continuous data transfer, particularly in the field of digital video and audio technology.

Typical applications include connecting DV camcorders, digital cameras or audio equipment with a corresponding FireWire interface. The cable supports data rates of up to 400 Mb/s and enables reliable transmission of audio and video data.

It is important to ensure the correct configuration of the connectors. The 4-pin connector transmits data only and does not provide a power supply. Connected devices must therefore be powered separately. This cable is intended solely for connecting compatible FireWire devices and is not suitable for other interfaces such as USB. No signal conversion takes place.

Connector 1: FireWire 4-pin plug

Connector 2: FireWire 6-pin plug

Standard: IEEE1394a

Maximum data transfer rate: 400 Mb/s

Length: 1.8 m