

InLine DisplayPort 2.1 cable, UHBR20 80 Gb/s, black, gold-plated contacts, 0.5m



Model: 15855P

Manufacturer: INLINE

EAN: 4043718350735

Product Code: 1552334

R858

UHBR20 for high-resolution image transmission at up to 80 Gb/s

High transmission performance: DisplayPort 2.1 with UHBR20 transmits data at up to 80 Gb/s and 20 Gb/s per lane.

High resolution and refresh rate: Supports 7680 x 2160 at 240 Hz with 4:4:4 and 10-bit colour depth, as well as 3840 x 2160 at up to 120 Hz with 4:4:4 and 12-bit colour depth.

Secure fit at the connector: The locking mechanism on both DisplayPort plugs protects the connection from accidental disconnection.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

High-quality connector: Gold-plated pins and gold-plated connector housings ensure reliable contact quality.

Versatile: The cable is suitable for high-performance monitor connections at workstations, in technical installations and in permanently installed systems.

The DisplayPort 2.1 cable is suitable for high-performance video connections between compatible devices with a DisplayPort connection. It supports applications with high resolutions and smooth image display. These include high-performance workstations, the display of detailed content and permanently installed monitor set-ups.

The high bandwidth supports demanding video signals. Content with fast-moving images can be displayed on compatible devices with high refresh rates. The locking mechanism on both connectors secures the cable firmly to the port. This is particularly advantageous for permanently installed systems and ports that are difficult to access.

DisplayPort male to DisplayPort male

Cable construction: 30 AWG conductor cross-section

Cable diameter: 7.3 ± 0.2 mm

Cable sheath: PVC, black

Kink protection sleeves: PVC, black

Connector housing: ABS, black

Connector insulation: blue

Shielding: AM and braided