



InLine 57885F KVM switch Rack mounting Black



Model: 57885F

Manufacturer: INLINE

EAN: 4043718344291

Product Code: 1552354

R3,034

Efficient control of two PCs with dual monitor setup: Operate two computers simultaneously via two HDMI monitors and shared USB peripherals.

High image quality with 4K60Hz support: Enjoy crystal-clear images in up to 4K@60Hz with full colour depth and HDR functionality.

Flexible control options for professional applications: Switching via hotkey, front button, IR remote control or RS-232 – ideal for individual working environments.

Maximum compatibility thanks to platform-independent technology: Works without drivers with Windows, macOS and Linux – ideal for mixed IT infrastructures.

Reliable operation thanks to sturdy metal housing: Robust construction and ESD protection ensure safe and long-lasting use in professional environments.

The InLine® KVM Switch, 2-port, HDMI, 4K60Hz, Dual Monitor, has been developed for professional users who want to efficiently operate two computers via a shared set of peripherals. With two HDMI outputs per PC, you can operate two monitors simultaneously – ideal for multitasking and parallel

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

work.

The device supports high-resolution image signals up to 4K@60Hz in full colour depth (4:4:4) including HDR, Dolby Vision and other modern video formats. Switching is convenient via hotkey, IR remote control, front button or RS-232 interface – just as you need it.

The integrated USB interface allows simultaneous access to keyboard, mouse, storage media or other USB 3.2 Gen.1 devices. Thanks to its driverless plug-and-play functionality, the KVM switch is ready for immediate use – across platforms under Windows, macOS and Linux.

Thanks to its high-quality metal housing, ESD protection and well-designed accessories, the device is perfect for control rooms, technical workstations or professional multi-system environments.

HDMI inputs: 4 × HDMI (2 per PC, A/B)

HDMI outputs: 2 × HDMI (display A and B)

USB ports: 2 × USB host (USB-B), 4 × USB 3.2 Gen.1 (USB-A)

Audio output: 3.5 mm stereo jack (PCM 2.0CH)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm stereo jack (38 kHz)

Resolution: up to 4K@60Hz, 2K@144Hz

Colour depth: 8 / 10 / 12 bits

Colour spaces: RGB, YCbCr 4:4:4, 4:2:2, 4:2:0

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

HDMI version: HDMI 2.0

HDCP compatibility: HDCP 2.3

Audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Latency: no video or audio delay

CEC support: yes

ESD protection: ±8 kV air / ±4 kV contact

Housing: metal housing, black

Dimensions: 220 × 100 × 30 mm

Weight: 626 g

Operating temperature: 0–40 °C

Storage temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Recommended HDMI cable lengths:

up to 5 m: 4K@60Hz (Premium High Speed HDMI)

up to 10 m: 1080p (standard HDMI cable)

External power supply (power adapter):

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average efficiency in operation: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Scope of delivery:

1 × InLine® KVM switch, 2-port, HDMI, 4K60Hz, dual monitor

1 × IR remote control

1 × IR receiver cable (1.5 m, 38 kHz)

2 × HDMI cables (1.5 m each)

2 × USB cables (USB 3.2 Gen.1, USB-A to USB-B, 1.8 m)

1 × 12 V/1 A power supply with lock

1 × 3-pin terminal connection plug

2 × mounting brackets

4 × screws (KM3×4)

1 × user manual in German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950