

InLine 57885H KVM switch Rack mounting Black



Model: 57885H

Manufacturer: INLINE

EAN: 4043718344314

Product Code: 1552355

R3,876

Conveniently control two PCs: Use one workstation with two monitors, one keyboard, one mouse and multiple USB devices for both computers.

Highest resolutions up to 8K@60Hz: Supports HDMI 2.1, HDR10, Dolby Vision and enables crystal-clear images for gaming, image editing or presentations.

Flexible switching without delay: Switch quickly between two PCs via hotkey, button, IR remote control or RS-232 – without reconnecting cables.

Integrated USB 3.2 hub: Four USB ports plus two hotkey USB ports for flexible use of keyboard, mouse and peripherals – ideal for versatile applications.

Robust metal housing and plug & play: Easy installation without drivers, high-quality design – perfect for professional and private use.

The InLine KVM Switch, 2-port, HDMI 2.1, Dual Monitor, 8K60Hz allows you to control two PCs from a single workstation with two monitors, one keyboard, one mouse and multiple USB devices.

Switching between the two computers is convenient via hotkey, button, IR remote control or RS-232

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

– without time-consuming cable reconnections. Thanks to HDMI 2.1 technology and a maximum resolution of 8K at 60Hz, you benefit from impressive image quality and smooth display.

The KVM switch supports HDR10, Dolby Vision and other modern video and audio formats – ideal for gaming, graphics editing, presentations or control rooms.

With four USB 3.2 Gen.1 ports and two additional hotkey USB ports, you can conveniently use a keyboard, mouse and other peripheral devices. The robust metal housing, high transmission bandwidth of up to 40 Gb/s and simple plug & play installation make the switch a future-proof solution for private and professional users.

Inputs:

- 4 × HDMI (2 per PC, type A, 19-pin)
- 2 × USB host (USB-B)

Outputs:

- 2 × HDMI (type A, 19-pin)
- 1 × L/R audio output (3.5 mm stereo)

Video resolutions: up to 8K@60Hz, 4K@120Hz/144Hz, 1080p@240Hz

Video bandwidth: up to 40 Gb/s

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

Colour depth: 8 / 10 / 12 bits

Colour spaces: RGB, YCbCr 4:4:4 / 4:2:2 / 4:2:0

HDMI version: HDMI 2.1

HDCP version: HDCP 2.3

Audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Latency: no video or audio delay

CEC support: yes

USB ports:

- 4 × USB 3.2 Gen.1 (USB-A)
- 2 × USB 3.2 Gen.1 (USB-A) with hotkey support (switchable to USB 1.1)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm jack socket

Housing: metal, black

Dimensions: 220 × 100 × 30 mm

Weight: 626 g

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating temperature: 0–40 °C

Storage temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

ESD protection: ± 8 kV air / ± 4 kV contact

Recommended cable lengths

up to 3 m: 8K / 4K@120Hz

up to 5 m: Ultra HDMI 2.1

up to 10 m: 1080p with standard HDMI cable

External power supply (power adapter)

Type: external plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average operating efficiency: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Scope of delivery

1 × InLine® KVM switch, 2-port, HDMI, 8K60Hz, dual monitor

1 × IR remote control

1 × IR receiver cable (1.5 m, 38 kHz)

2 × USB cable (USB 3.2 Gen.1, USB-A to USB-B, 1.8 m)

4 × HDMI cables (1.5 m each, plug/plug)

1 × 12 V/1 A power supply with lock

1 × 3-pin terminal connection plug

2 × mounting brackets

4 × screws (KM3×4)

1 × user manual in German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950