

InLine 16759A power cable Black 1 m IEC C14 Schuko



Model: 16759A

Manufacturer: INLINE

EAN: 4043718352425

Product Code: 1552531

R867

C14 angled to earth-contact adapter cable for space-saving power connections

Space-saving installation thanks to the angled plug:The angled C14 connector reduces the required installation depth and makes cable routing easier in compact environments.

Flexible use of C14 power sources:Enables the connection of devices with earthed plugs to existing C14 sockets without modifying the infrastructure.

Reliable power transmission up to 10 A:Designed for a stable power supply in typical IT and technical applications.

Optimised cable lengths for structured cabling:Available in 0.5 m, 1 m, 2 m and 3 m for a neat and tailored installation.

Adjusted conductor cross-section depending on length:Up to 2 m with 3 x 0.75 mm², and 3 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

with 3 x 1.00 mm² for a reliable supply even over longer distances.

This InLine® mains adapter cable with an angled C14 plug for IT equipment to a grounded socket offers a space-saving solution for connecting devices to existing C14 power sources. The angled plug reduces the required installation depth and facilitates installation in confined spaces.

The cable enables the flexible operation of devices with earthed plugs on C14 sockets without the need to modify existing power distribution systems. This allows existing connection points to be utilised efficiently.

With a current rating of up to 10 A, the adapter cable is suitable for many typical applications. The various length options, ranging from 0.5 m to 3 m, support structured and clearly organised cable routing.

Depending on the variant, a conductor cross-section of 3G0.75 mm² or 3G1.00 mm² is used. This ensures reliable power transmission even over longer cable runs.

Connection A: C14 for IT equipment, angled

Connection B: EARTH-connected socket

Rated current: 10 A

Conductor cross-section 0.5 m / 1 m / 2 m: 3G0.75 mm²

Conductor cross-section 3 m: 3G1.00 mm²

Lengths: 0.5 m, 1 m, 2 m, 3 m