



InLine 92504A wire connector USB-A / Terminal block, 5-pin Black, Green

Model: 92504A

Manufacturer: INLINE

EAN: 4043718346103

Product Code: 1553034

R825

Time savings during installation: Quick wiring via screw terminals for 16–26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Clear terminal assignment & secure contact: 5-pin terminals with pressure plate, clearly labeled 1: –, 2: D+, 3: D–, 4: +, 5: S (shield) – ideal for service, testing, and prototyping.

Versatile industrial use: For quick connection of USB 2.0 signals in test setups, laboratories, commissioning, or troubleshooting – no soldering required.

Compact design: Only approx. 50 mm total length; can also be integrated into tight setups or adapter strips to save space.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.7 A per pin ensure reliable signal transmission – even under continuous load and in industrial environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® USB-A terminal block adapter offers a practical solution for transferring USB-2.0 signals to a 5-pin terminal block without soldering or cable connection. Typical applications can be found in the areas of service, test setups, development, or prototyping.

The standard-size USB-A connector is directly connected to a 5-pin screw terminal block. The clear labeling of the terminals – 1: Ground (-), 2: D+, 3: D-, 4: Voltage (+), 5: Shield (S) – enables easy and reliable signal assignment. The terminal connections with a 5.0 mm grid dimension support single wires in the 16–26 AWG range.

Wiring is carried out with the aid of a flat-head screwdriver. Thanks to its compact housing, the adapter is particularly space-saving – e.g. in test equipment, mobile measuring stations, or in laboratories.

USB interface:USB-A 2.0, plug

Number of pins / assignment:5 terminals / 1: - / 2: D+ / 3: D- / 4: + / 5: S

Connection technology:Screw terminal with pressure plate, 5.0 mm pitch

Connection range:16–26 AWG

Actuation:With flat-blade screwdriver ≤ 2.5 mm

Rated current:0.7 A per pin

USB operating voltage (VBUS):5 V DC

Test voltage (insulation resistance):300 V AC / 1 minute

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature:-20 °C to +105 °C

Insulation layer:EVA insulation on underside

Dimensions:approx. 50 × 21 × 14 mm (L × W × H)