InLine 92504H wire connector USB-A / Terminal block, 5-pin Black, Green

Model: 92504H

Manufacturer: INLINE

EAN: 4043718346172

Product Code: 1553038

R886

Time savings during installation: Quick wiring via screw terminals for 16–26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Integrated USB cable for flexible applications: The 1-meter connection cable connects systems immediately – without additional accessories or soldering.

Clear terminal assignment & secure contact: 5-pin terminals with pressure plate, clearly labeled 1: –, 2: D+, 3: D–, 4: +, 5: S (shield) – ideal for service, testing, and prototyping.

Versatile use in industry: For fast connection of USB 2.0 signals in test setups, laboratories, commissioning, or troubleshooting – without soldering.

High signal quality: An insulation resistance of ≥ 10 MΩ at 300 V DC and a rated current of 0.7 A per pin ensure reliable signal transmission – even under continuous load and in industrial environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The InLine® USB-A 2.0 terminal block adapter with socket and permanently integrated connection cable enables easy connection of USB signals to a 5-pin screw terminal strip – without any soldering. The terminals are clearly labeled (1: ground, 2: D+, 3: D–, 4: voltage, 5: shield) and support wires in the range of 16–26 AWG. Tool-assisted wiring is performed using a flat-head screwdriver ≤ 2.5 mm. With a cable length of 1 meter, the adapter is ideal for test setups, laboratory environments, or embedded systems. An EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces.

USB interface:USB-A 2.0, female connector
Cable length:approx. 1 m (PVC, permanently integrated)
Number of pins / assignment:5 terminals / 1: – / 2: D+ / 3: D– / 4: + / 5: S
Connection technology: Screw terminal with pressure plate, 5.0 mm pitch
Connection range:16–26 AWG
Actuation: With flat-blade screwdriver ≤ 2.5 mm
Rated current: 0.7 A per pin
USB operating voltage (VBUS):5 V DC
Test voltage (insulation resistance):300 V AC / 1 minute
Insulation resistance:≥ 10 MΩ @ 300 V DC
Operating temperature:–20 °C to +105 °C
Insulation layer:EVA insulation on underside
Dimensions: Terminal block approx. 50 × 21.2 × 18.4 mm (L × W × H)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950