



Lanview RWP16U45BL-D rack cabinet 16U Wall mounted rack Black



Model: RWP16U45BL-D

Manufacturer: LANVIEW

EAN: 5715063210604

Product Code: 1557261

R11,141

Product Dimensions:

Rack: WxDxH(mm): 600 x 450 x 817mm

Double wallmount section: WxDxH(mm): 600x150x809

Colored strips located at the sides of the 4mm, antistatic, tempered, smoothed glass, door having an extruded aluminum frame and high fracture resistance present a decorative view.

The double wall mounted back section allows for installation of further 19" compatible equipment, ideal for housing cable harnesses, patch panels and other equipment. with the cable inlet hole in the back it is ideal to feed cables through. Equipments, conforming with 19" installation and of 70mm depth, may be attached inside the double wall mounting section.

By attaching ventilation module with 2 fans maximum (in option) to the ventilation hole at the upper chassis of the cabinet, active ventilation is achieved. If no fan module is attached, these ventilation holes enable air circulation inside cabinet and discharging of the hot air by passive ventilation.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Since the side panels are detachable, access to the cabinet is ensured both from the front and sides in wall mounting applications and from the all sides in free standing applications.

Standard cabinet is delivered having 1 set and 2 device installation rails mounted thereon. Device installation rails enable the depth adjustments of the devices to be applied into the cabinet.

By means of 145mm x 70mm cable inlet holes at the upper, lower and rear door of the cabinet, it provides cable inlet at 3 directions which in turn facilitates installation.

Thanks to the rubber edged cable entry module, movable for 0-50 mm and with sliding compression system, incoming cables are compressed safely whereas dust is reduced inside at maximum levels.

This item number consists of two parts: RWP16U45BL + RWMD16UBL