



InLine Gigabit Network Switch 16-Port, 1Gb/s, 19" 1U, fanless



Model: 323110

Manufacturer: INLINE

EAN: 4043718298112

Product Code: 1558610

R2,996

16-port gigabit switch for reliable network expansion with 1 Gb/s per port with **auto-negotiation Plug & Play and Auto MDI/MDI-X crossover detection**– Each individual port automatically detects the speed of the connected devices

Green IT: Energy-saving thanks to IEEE 802.3az Energy Efficient Ethernet through cable length detection and automatic signal strength

Store-and-forward switching to avoid corrupted packets

Freightless 19" 1U housing for low noise operation

The InLine® 16-port Gigabit network switch is a powerful and uncomplicated solution for expanding existing network infrastructures. Each of the sixteen RJ45 ports automatically detects the speed of the connected devices (10/100/1000 Mb/s) and adapts flexibly in half or full duplex mode. Thanks to Auto-MDI/MDI-X, the type of network cable used is irrelevant. The store-and-forward technology ensures efficient forwarding of data packets and prevents the transmission of faulty data.

With IEEE 802.3az Energy Efficient Ethernet (EEE), cable lengths and network activities are detected

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

to dynamically reduce energy consumption - ideal for sustainable IT environments.

The switch is designed to be fanless and therefore quiet in operation, perfect for office, laboratory or server rack environments. The 19-inch rack mounting in 1U enables easy integration into existing structures.

Technical specifications:

16x RJ45 ports, 10/100/1000Base-T, Auto-MDI/MDI-X

Chipsätze: RTL8382L + RTL8218D + 2x RTL8231

Standards: IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.3az

Store-and-forward switching

MAC address table: 8K, auto-learning & auto-update

Jumbo frame: 9216 bytes

Bandwidth: 32 Gbit/s

LED indicators: PWR, LNK/ACT

Network cable: Cat. 5/5e or higher (up to 100 m)

Dimensions: 480 x 180 x 44 mm

Weight: approx. 2.15 kg

Power supply: 100–240V AC, 50/60 Hz

Max. Power consumption: 21 W

Operating temperature: 0–40 °C

Storage temperature: -40–70 °C

Humidity: operation 10–90 %, storage 5–90 % (non-condensing)

Scope of delivery:

1x InLine® PoE+ Gigabit network injector hub 8 port

2x operating instructions (German/English)

1x power supply

2x 19" mounting bracket

6x screws for the mounting brackets

4x rubber feet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950