



InLine 23156Q holder Passive holder Mobile phone/Smartphone Black, Multicolour

Model: 23156Q

Manufacturer: INLINE

EAN: 4043718337491

Product Code: 1558835

R1,307

Universal car holder with wireless charging function up to 15 W

Smart sensor technology for automatic opening and closing of the holder arms

Three mounting options: Ventilation (hook/clamp) or suction cup

Integrated Farad capacitor enables up to three openings when the vehicle is switched off

Integrated protection mechanisms: Overvoltage, overheating, FOD detection

The InLine® ONE TOUCH Qi 2 is the new generation of our successful smartphone cradles for professional vehicle use. It offers modern wireless charging technology up to 15 W according to the Qi standard and impresses with its smart operation and versatile mounting options. Power is supplied via USB-C - ideal for use in IT-supported mobility solutions or vehicle fleets.

The integrated sensor system ensures that the holding arms close automatically as soon as the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

smartphone is inserted. A simple touch is all it takes to open them - conveniently and safely, even while driving. Thanks to the Farad capacitor, the holder retains its function even when the vehicle is switched off: Up to three opening/closing operations are possible without any problems. The smartphone will not continue to charge in this state.

The holder can be attached either by suction cup or to the air vents - depending on the vehicle type or user requirements. Overvoltage, overheating and foreign object detection ensure maximum operational safety.

Input voltage: DC5.0V / 2.0A, DC9.0V / 1.67A, DC12.0V / 1.67A

Wireless output: 5W / 7.5W / 10W / 15W (max. 9.0V / 1.7A)

Frequency: 110-205kHz

Charging distance: ≤ 8 mm

Charging efficiency: ≥ 75 %

Dimensions: approx. 76 × 122 × 60 mm

Weight of the holder: approx. 125 g

Weight of suction cup base: approx. 110 g

Weight of hook base: approx. 20 g

Weight of the clamp base: approx. 40 g

Operating temperature: 0-45 °C

Storage temperature: -10-60 °C

Humidity: 20-95 %, non-condensing