

TP-Link EAP727 Access Point



Model: EAP727

Manufacturer: TP-LINK

EAN: 1210002620062

Product Code: 1563093

R4,109

5 GHz: Yes | Security algorithms: WPA3-Personal | Security algorithms: WPA3-Enterprise | Antenna type: Internal | Reset button: Yes | Width: 160 mm | Power over Ethernet (PoE): Yes | Maximum data transfer rate (5 GHz): 4324 Mbit/s | Power consumption (max): 15.6 W | Quantity per pack: 1 pc(s) | DC-in jack: Yes | Antenna gain level (max): 6 dBi | Operating altitude: 0 - 2000 m | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | MAC address filtering: Yes | Ethernet LAN (RJ-45) ports: 1 | Networking standards: IEEE 802.1AX | Security algorithms: WPA-Personal | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA-Enterprise | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Product colour: White | Networking standards: IEEE 802.11ac | Antenna features: Integrated antenna | Security algorithms: WPA2-Personal | Antennas quantity: 5 | Weight: 470 g | Placement: Ceiling, Wall | Bluetooth: Yes | 2.4 GHz: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Compliance certificates: CE | Compliance certificates: VCCI | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: ICES | Compliance certificates: JRF | Fast roaming: Yes | Number of simultaneously connected devices (max): 510 | Remote Authentication Dial-In User Service (RADIUS): Yes | Cloud-managed: Yes | Ethernet LAN: Yes | Depth: 160 mm | Management protocols: SNMP v1, v2c, v3 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Service Set Identifier (SSID) features: Multiple SSIDs | Band steering: Yes | Non-operating altitude: 0 - 2000 m | Channel bandwidth: 160 MHz | Number of users: 510 user(s) | BeamForming: Yes | Schedule access: Yes | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | VLAN support: Yes | Wall mountable: Yes | Wi-Fi roaming: Yes | Number of SSID supported: 16 | Height: 36.7 mm | Airtime Fairness (ATF): Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Coverage area: 185 m² | Wireless meshing: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950