



Mikrotik
CRS326-24G-
2S+RM network
switch L2
Gigabit Ethernet
(10/100/1000)
Grey (CRS326-
24G-2S+RM)

Model: CRS326-24G-2S+RM

Manufacturer: MIKROTIK

EAN: 5902560367560

Product Code: 1576699

R5,050

Mikrotik CRS326-24G-2S+RM network switch L2 Gigabit Ethernet
(10/100/1000) Grey

CRS326-24G-2S+RM

This is a SwOS/RouterOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features!

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The "Dual boot" feature that allows you to choose which operating system you prefer to use, RouterOS or SwOS. If you prefer to have a simplified switch only OS with more switch specific features, use SwOS. If you are used to Winbox and would like the ability to use routing and other Layer 3 features on some ports in your CRS, boot and use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings.

It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

Additional Product Notes

- 1. Non-blocking Layer 2 switching capacity
- 2. 16K host table
- 3. IEEE 802.1Q VLAN
- 4. Supports up to 4K VLANs
- 5. Port isolation
- 6. Port security
- 7. Broadcast storm control
- 8. Port mirroring of ingress/egress traffic
- 9. Rapid Spanning Tree Protocol
- 10. Access Control List
- 11. MikroTik neighbor discovery
- 12. SNMP v1
- 13. Web-based GUI

CPU	RAM	Storage type	10/100/1000 Ethernet ports	Dimensions	Max power consumption	Serial port
98DX3236A1 800 MHz	512 MB	16 MB	24	443 x 144 x 44 mm	24 W	RJ45