

Protect Viewport



Model: UP-Viewport

Manufacturer: UBIQUITI

EAN: 8178820295752

Product Code: 1579414

R6,335

STREAMLINED VIEWING EXPERIENCE FOR PROTECT CAMERAS

The Ubiquiti Protect Viewport serves as an intuitive hub designed specifically for viewing Protect camera feeds on any HDMI display. With its compact dimensions of 157 x 52 x 37 mm (6.2 x 2.1 x 1.5 inches) and lightweight design, it seamlessly integrates into various environments, making it an ideal solution for both home and business security monitoring. The device's user-friendly interface ensures that accessing live feeds is straightforward, allowing users to stay connected to their security system effortlessly.

ROBUST BUILD AND RELIABLE PERFORMANCE

Constructed from durable polycarbonate, the Protect Viewport is built to withstand everyday use while maintaining a sleek appearance. It features a single GbE RJ45 port for reliable networking and supports Power over Ethernet (PoE), simplifying installation by reducing the need for additional power sources. With a maximum power consumption of just 9.5W, it operates efficiently without compromising performance. The device is also equipped with ESD/EMP protection, ensuring it

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

remains operational in various conditions.

VERSATILE COMPATIBILITY AND COMPLIANCE

The Ubiquiti Protect Viewport is designed to work seamlessly with the UniFi Protect web application and mobile app, available for both iOS and Android devices. This compatibility allows users to monitor their security feeds from anywhere, enhancing the overall user experience. Additionally, the device is NDAA compliant and certified by FCC, IC, CE, and Anatel, ensuring it meets stringent regulatory standards for safety and performance. With an operating temperature range of 0 to 40° C (32 to 104° F) and humidity tolerance of 20 to 80% noncondensing, it is suitable for a variety of environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950