

InLine Slim SAS cable, SFF-8654 to U.2 SFF-8639 + SATA power, 24Gb/s, 0.5m

Model: 27644A

Manufacturer: INLINE

EAN: 4043718288601

Product Code: 1580169

R1,473

Fast U.2 connection: Supports data rates of up to 24Gb/s per channel for reliable transmission of modern SSDs.

Sophisticated combination solution: Combines data and power supply with SFF-8639 and SATA power connectors – ideal for space-saving installations.

High compatibility: Suitable for SAS 4.0 controllers with SFF-8654 connection – efficiently connects U.2 SSDs.

Secure hold: Lockable slim SAS connector for a secure fit even with vibrations during server operation.

Optimized for server environments: Ideal for workstations, JBOD setups, RAID systems, and data centers.

The InLine® Slim SAS cable with U.2 SFF-8639 connector and additional SATA power connector

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

offers a powerful and sophisticated connection solution for use in professional storage environments. It connects a Slim SAS 4i connector (SFF-8654) to a U.2-compatible connector (SFF-8639) and a SATA power supply.

With support for up to 24Gb/s per channel, this cable is ideal for connecting modern U.2 SSDs to SAS controllers, HBA cards, or RAID systems. The combination of data and power connection saves space in the enclosure and enables particularly clean cabling—especially in cramped server configurations. The lock on the Slim SAS connector ensures a secure hold even during continuous use and vibrations. Compliant with SAS 4.0 specifications, the cable ensures reliable performance in demanding applications in data centers, workstations, or storage solutions.

Interfaces:SFF-8654 (Slim SAS 4i) to SFF-8639 (U.2) + SATA power

Standard:SAS 4.0

Data rate: Up to 24Gb/s per channel

Feature: Combination connector with data and power connection

Type: Internal connection cable for U.2 SSDs

Variant:27644A = 0.5 m, 27644B = 1 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950