

InLine MCIO x8 breakout cable to 8x SATA, 1 m



Model: 27665C

Manufacturer: INLINE

EAN: 4043718353439

Product Code: 1580953

R1,463

Efficient connection of multiple SATA drives to an MCIO x8 host connector

Space-saving storage connection: Connects an MCIO x8 (SFF-TA-1016) host connector to up to eight SATA drives via a single breakout cable.

Flexible integration: Suitable for use with server motherboards, RAID controllers and tri-mode HBAs featuring an MCIO interface.

Supports SATA data connections: Enables the connection of up to eight SATA HDDs or SATA SSDs via a single MCIO x8 port.

Reliable signal transmission: The high-quality construction ensures a stable data connection in professional storage environments.

The InLine® MCIO x8 breakout cable connects an MCIO x8 (SFF-TA-1016) host connector to up to eight SATA drives. It is suitable for systems in which multiple SATA HDDs or SATA SSDs are to be

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

connected via a compact cabling solution.

By splitting a single MCIO x8 connector across eight SATA 7-pin connectors, the cable reduces the amount of cabling required within the system and facilitates a tidy installation. It is designed for use with server motherboards, RAID controllers and tri-mode HBAs featuring an MCIO interface.

The breakout cable supports SATA data connections and is available in lengths of 0.5 m, 0.75 m and 1 m. The high-quality construction ensures reliable signal transmission.

MCIO x8 (SFF-TA-1016) 74-pin connector to 8x SATA 7-pin connectors

For connecting up to eight SATA HDDs or SATA SSDs

Suitable for servers, workstations, RAID controllers and tri-mode HBAs

Supports SATA data connections

High-quality construction for reliable signal transmission

Temperature range: -20 °C to +80 °C

Humidity: 0–90 per cent, non-condensing

Length options: 0.5 m / 0.75 m / 1 m