

D-Link 28-Port Gigabit Stackable PoE+ Smart Managed Switch with 4 x 10G SFP+ Ports



Model: DGS-1530-28P/E

Manufacturer: D-LINK

EAN: 790069474590

Product Code: 1584562

R19,058

Uninterrupted Service

Redundant power supply ensures uninterrupted operation while boosting PoE output for high-demand devices

Simplified Management

The SIM feature lets you manage multiple switches as a virtual stack under one IP, streamlining operations and integration

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Enhanced Security

Features includes VLANs, ACLs, Port Security, 802.1X, and RADIUS to protect data and manage access

Resilience Connectivity

G.8032 ERPS delivers sub-millisecond ring recovery for uninterrupted connectivity across critical operations

Seamless Power Delivery

PD-Alive, Fast PoE, and Perpetual PoE ensure rapid startup, automatic device recovery, and uninterrupted power supply

Shielded for Stability

All copper ports include 6kV surge protection for reliability and protection against electrical spikes

Zero-Touch Setup, Infinite Scalability

Zero-Touch Provisioning (ZTP) streamlines setup by enabling devices to auto-configure without manual input. Simply hold the reset button for 5-10 seconds to trigger reboot and provisioning. ZTP speeds up deployment, minimizes errors, and ensures consistent configuration and ideal for large-scale networks.

Power on the switch and connect the cable to service LAN, then start ZTP

- Hold the reset button (5~10 sec)
- Get IP and settings from DHCP server
- Download firmware or configuration from TFTP server

Effortless PoE for Modern Networks

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The DGS-1530-28P supports 802.3af/at PoE standards, delivering up to 30 W per port and a PoE budget of 370 W with Perpetual and Fast PoE.

PoE enables the simple deployment of IP cameras, APs, and VoIP phones over standard Ethernet, reducing the need for separate electrical wiring and allowing owners to tailor power availability for their business venues.

Recover Instantly with Intelligent Stacking

Physical stacking lets multiple switches act as one, boosting scalability and resilience. It reroutes traffic automatically during failures, supports hot-swapping, and ensures seamless master switch failover. Shortest-path forwarding and trunked ports enhance bandwidth and reliability.

Smarter Multicast for Seamless Streaming

The rise of IPTV and multimedia streaming, efficient multicast management is crucial. IGMP/MLD snooping prevents duplicate streams and interference between STBs within the same VLAN, while ISM VLAN reduces redundant multicast traffic across VLANs—enhancing backbone efficiency and ensuring smoother streaming performance.