Switch UBIQUITI 180 Watts USW-PRO-MAX-16-POE

Model: USW-PRO-MAX-16-POE

Manufacturer: UBIQUITI

EAN: 810084694572

Product Code: 1590298

R9,822

A 16-port, Layer 3 Etherlighting™ switch with 2.5 GbE, PoE++ output, and versatile mounting options.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network
- (4) 2.5 GbE PoE++ ports
- (12) GbE PoE+ ports
- (2) 10G SFP+ ports
- 180W total PoE availability
- Versatile desktop, wall, and rack mounting
- Silent, fanless cooling system

Summary: Ubiquiti Pro Max 16 PoE. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

16. Switching capacity: 84 Gbit/s. Networking standards: IEEE 802.1x. DC input voltage: 44 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting | Vendor Homepage: https://eu.store.ui.com/eu/en/pro/category/switching-professional-max/products/usw-pro-max-16-poe | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L3 | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 16 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (varinis) portų kiekis: 12 | 2,5 Gb eterneto (laidinių) lizdų skaičius: 4 | SFP+ modulio angų kiekis: 2 | Maitinimo jungtis: DC lizdas | Tinklo standartai: IEEE 802.1x | 10G parama: Taip | Portų mirroring: Taip | Reitingo apribotojimas: Taip | Srauto kontrolės palaikymas: Taip | Transliacijos audros valdymas: Taip | VLAN palaikymas: Taip | Virtualaus vietinio tinklo ypatybės: Voice VLAN | Perjungimo pajėgumas: 84 | Pralaidumas: 42 | Persiuntimo dažnis: 62.496 | Jumbo Frames palaikymas: Taip | DHCP funkcijos: DHCP snooping/DHCPv6 relay | IGMP tinklinio judėjimo sekimas: Taip | Apsauga nuo nesklandaus ryšio: Taip | Multicast palaikymas: Taip | Stovo montavimas: Taip | Produkto spalva: Pilka | Korpuso medžiaga: Plienas | Atstatymo mygtukas: Taip | LED indikatoriai: Sistema | Ekrano tipas: LCM | Maitinimo šaltinis: AC/DC | Pridėtas maitinimo šaltinis: Taip | Nereikalingos maitinimo (RPS) paramos: Taip | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50/60 | DC įėjimo įtampa: 44 - 57 | Galios suvartojimas (maks.): 30 | Maitinimas per Eternetą (PoE): Taip | Maitinimo per Eternetą plius (PoE+) prievadų skaičius: 12 | Maitinimo eternetu 4PPoE (PoE++) jungčių skaičius: 4 | Maitinimo per Eternetą (PoE) galia prievadui: 15 | Bendrosios galios per Eternetą (PoE) charakteriskos: 180 | Darbo temperatūros diapazonas (TT): -5 - 40 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Plotis: 325.1 | Ilgis: 160 | Aukštis: 43.7 | Svoris: 2100 | Pridėti kabeliai: Energija | Instrukcija: Taip | Pridėti montavimo kronšteinai: Taip | Atitikties sertifikatai: CE/Federalinė ryšių komisija (FCC)/Industry Canada (IC) | Bruto svoris: 4.08 | Neto svoris: 2.1 | Vienetų skaičius vienoje siuntimo dėžėje: 4 | Vieneto plotis: 25 | Shipping Box Height: 25.5 | Vieneto gylis: 51.5 | Vieneto aukštis: 11 | Name: NET SWITCH 16PORT 2.5GBE/USW-PRO-MAX-16-POE UBIQUITI | Model: USW-PRO-MAX-16-POE | Model name: Pro Max 16 PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950