

3M 4251+ One Size 1 pc(s)



Model: 7100113098

Manufacturer: 3M

EAN: 4054596256156

Product Code: 1597135

R1,615

3M™ Maintenance Free Half Mask 4251+ is a simple and ready-to-use respirator with an integrated cartridge and filters. A newly enhanced valve assembly helps to reduce exhalation breathing resistance, and the close-fitting, non-silicone, textured face seal is soft and non-allergenic. Includes a resealable bag for hygienic storage and transportation.

Get effective, easy-to-use and fully-assembled breathing protection with 3M™ Maintenance Free Half Mask Respirator 4251+, with a newly enhanced valve assembly which helps to reduce exhalation breathing resistance for improved breathing comfort. Our respirator has a textured face seal that's soft, non-allergenic and silicone free, and provides FFA1P2 R D protection against a range of organic gases and vapours, and combination particulate hazards. The lightweight, well-balanced design features a centrally-positioned exhalation valve that helps reduce heat and moisture build up, helping you to stay comfortable in hot and humid conditions. The integrated cartridge and filters are maintenance free; simply use until your change-out schedule indicates a replacement is needed or when the filters are full, and then discard. It will give you up to 40 hours of use life when stored in the resealable bag provided. An adjustable head cradle helps fit to a broad range of head shapes and sizes, and the neck straps are easy to fasten. The low-profile design won't hinder your peripheral vision, and the two large, bonded-carbon filters provide low breathing resistance. FFA1P2 R D

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

protects against organic vapours, with a boiling point greater than 65 °C, up to 10 x Workplace Exposure Limit (WEL) or 1000 ppm (whichever is lower), and 10 x WEL for particulates.