

Lindy 4K60 HDMI and USB SDVoE Transceiver



Model: 38365

Manufacturer: LINDY

EAN: 4002888383653

Product Code: 1597726

R22,391

SDVoE is a globally recognised standard for high quality distribution of AV content with other features, including control, matrix, video wall and multi view over longer distances via 10G Network with no compressions and latency.

The Lindy 4K60 HDMI and USB SDVoE Transceiver is a high performance AV over IP Extender for HDMI 4K60, USB, Audio, IR and RS-232 signals. It can be set either as Encoder and Decoder in order to manage a full SDVoE installation while the connection with a 10G Network Switch can be done via copper with a standard Cat.6 or above cable, or adding a SFP+ fiber optic module (not included).

Supporting resolutions up to 4K Ultra HD, uncompressed video can be viewed in stunning clarity, while additional support for HDR (High Dynamic Range) allows content to be displayed with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut.

This unit provides different features connecting in multicast mode such as seamless switching, Video

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Wall up to 9x9 and Multiview up to 25 windows.

Device management can be done with Lindy SDVoE Controller (No.38364) providing a web based visual interface with signal preview and drag-and-drop operations making setup of the installation fast and intuitive. The management can be done also through any SDVoE codec, enabling compatibility with other software and hardware streaming platforms.

In addition to HDMI signal, this Transceiver supports bi-directional IR control, USB 2.0 to connect mouse, keyboard and other USB devices, 3.5mm analog stereo for embedding and extracting audio, RS-232 control and PoE.

Please note: this unit works only when connected to a 10Gigabit network. It can be controlled with any SDVoE controller system with API support.