

Thermaltake Toughpower PT 1000W power supply unit 24- pin ATX ATX Black



Model: PS-TPP-1000FNFAPE-1

Manufacturer: THERMALTAKE

EAN: 4711658545206

Product Code: 1610476

R3,798

Power protection features: Over power | Power protection features: Short circuit | Power protection features: Over voltage | PCI Express power connectors (6+2 pin): 5 | Bearing technology: FDB | Peripheral (Molex) power connectors (4-pin): 4 | Power protection features: Under voltage | Power protection features: Over current | Cabling type: Fully-Modular | Combined power (-12V): 3.6 W | On/off switch: Yes | ATX version: 3.1 | Operating relative humidity (H-H): 20 - 90% | Fan diameter: 13.5 cm | Purpose: PC | Cooling type: Active | Efficiency: 92% | Number of fans: 1 fan(s) | 80 PLUS certification: 80 PLUS Platinum | Hold time: 17 ms | Power supply unit (PSU) form factor: ATX | Total power: 1000 W | Safety: CE/UKCA/FCC/ICES/CB/TUV/cTUVus/LVD/CCC/BSMI/ S-MARK/EAC/RCM | Combined power (+3.3V): 110 W | Storage relative humidity (H-H): 5 - 95% | Depth: 140 mm | Power Factor Correction (PFC) type: Active | Combined power (+12V): 999.6 W | Height: 86 mm | Combined power (+5V): 110 W | Mean time between failures (MTBF): 100000 h | Combined power (+5Vsb): 15

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

W | Width: 150 mm | Max output current (+3.3V): 20 A | Storage temperature (T-T): -20 - 70 °C | Operating temperature (T-T): 0 - 40 °C | AC input voltage: 100 - 240 V | Input current: 15 A | Product colour: Black | Max output current (+12V): 83.3 A | CPU power cable length: 70 cm | Peripheral (Molex) power cable length: 450 | Peripheral (Molex) power cable length: 600 | Max output current (-12V): 0.3 A | CPU power connector (4+4 pin): Yes | AC input frequency: 47 - 63 Hz | Peripheral (Molex) power cable length: 750 | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 6 | Package type: Box | SATA power cable length: 450 | Max output current (+5V): 20 A | SATA power cable length: 750 | Power Good signal delay range: 100 - 150 ms | Motherboard power connector: 24-pin ATX | Peripheral (Molex) power cable length: 300 mm | Motherboard power cable length: 55 cm | SATA power cable length: 600 | PCI Express power connectors (12+4 pin): 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950