

Thermaltake Toughpower PT 1200W power supply unit 24- pin ATX ATX Black



Model: PS-TPP-1200FNFAPE-1

Manufacturer: THERMALTAKE

EAN: 4711658545305

Product Code: 1610477

R4,190

ATX version: 3.1 | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Over power | Cabling type: Fully-Modular | Number of fans: 1 fan(s) | Peripheral (Molex) power connectors (4-pin): 4 | Storage relative humidity (H-H): 5 - 95% | Fan diameter: 13.5 cm | Operating temperature (T-T): 0 - 40 °C | Cooling type: Active | PCI Express power connectors (6+2 pin): 5 | Total power: 1200 W | Efficiency: 92% | AC input frequency: 50/60 Hz | Bearing technology: FDB | Depth: 140 mm | Height: 86 mm | Width: 150 mm | Combined power (+3.3V): 100 W | Safety: CE/UKCA/FCC/ICES/CB/TUV/cTUVus/LVD/CCC/BSMI/ S-MARK/EAC/RCM | Package type: Box | Power supply unit (PSU) form factor: ATX | Product colour: Black | Storage temperature (T-T): -20 - 70 °C | Operating relative humidity (H-H): 20 - 90% | Input current: 15 - 10 A | On/off switch: Yes | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 100000 h | Purpose: PC | 80 PLUS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

certification: 80 PLUS Platinum | Max output current (+12V): 100 A | Power Factor Correction (PFC) type: Active | SATA power cable length: 600 | CPU power connector (4+4 pin): Yes | Power Good signal delay range: 100 - 150 ms | Motherboard power connector: 24-pin ATX | Combined power (+5Vsb): 15 W | SATA power cable length: 750 | SATA power cable length: 450 | Max output current (+5V): 20 A | Combined power (+12V): 1200 W | Hold time: 17 ms | Combined power (-12V): 3.6 W | Number of SATA power connectors: 6 | Max output current (+5Vsb): 3 A | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | Peripheral (Molex) power cable length: 600 | Peripheral (Molex) power cable length: 750 | Peripheral (Molex) power cable length: 450 | CPU power cable length: 70 cm | Peripheral (Molex) power cable length: 300 mm | Motherboard power cable length: 55 cm | Max output current (-12V): 0.3 A | PCI Express power connectors (12+4 pin) cable length: 600 mm | PCI Express power connectors (12+4 pin): 2

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950