



Lindy 50m Cat.6 HDMI 4K60 and IR Extender with PoC and Loop Out



Model: 38205

Manufacturer: LINDY

EAN: 4002888382052

Product Code: 1637056

R3,673

The Lindy Cat.6 HDMI 4K60 and IR Extender with PoC is an effective, reliable solution for extending high quality 4K HDMI signals over distances up to 50m (164.04ft) with standard Cat.5e/6 network cable. Support for the HDMI 2.0 18G specification allows the transmission of highly detailed 4K Ultra HD resolutions. With support for High-Dynamic Range, video content can be seen with enhanced brightness, greater contrasts of blacks and whites and a much wider colour gamut, perfect for a true home cinema experience or eye-catching digital signage in retail settings. HDCP 2.2 compliance allows 4K video content from copy protected sources such as Blu-Ray movies, media players and streaming services to be viewed without compatibility issues. Support for lossless audio formats including DolbyTrueHD and DTS-HD adds powerful multi-channel sound to video content, providing an enhanced experience and sense of realism for the viewer.

The extender features an HDMI loop-through output on the transmitter which allows for simultaneous

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

viewing using local and remote displays. This versatility provides a suitable solution for use in various scenarios such as educational presentation systems, home cinema, entertainment systems, or trade shows. The built in EDID dip switch enables the user to control which EDID is taken from either display, making installation and configuration simple ensuring maximum compatibility with HDMI displays and projectors. PoC allows both power and data signals over a Cat.6 cable in a point to point configuration, adding flexibility as only one power supply is required for both the transmitter and receiver units. Ideal when power outlets are limited.

Featuring IR Pass-through, the source equipment can be seamlessly controlled from the remote displays side of the installation using compatible infrared remote controls. This provides simple and complete control for the user.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.