



InLine USB Display Cable, USB-C male to DisplayPort male, 2m

Model: 64122

Manufacturer: INLINE

Product Code: 1660983

R2,413

High 4K performance at 60 Hz: Supports resolutions up to 3,840 x 2,160 @60Hz with RGB and YCbCr 4:4:4 – ideal for detailed displays.

Direct connection without adapters: USB-C plug to DisplayPort plug – for easy connection to DisplayPort monitors.

Thunderbolt 3 compatible: Also works with Thunderbolt 3 ports – for versatile use.

Wide operating system compatibility: Supports Windows 7/8/10 and macOS from version 10.9 – flexible use.

Durable and convenient: Gold-plated contacts, USB powered and Plug & Play – for reliable connections in daily use.

The InLine USB-C to DisplayPort cable is a versatile connection solution for connecting modern devices with a USB-C interface to DisplayPort monitors. It enables the reliable transmission of high-resolution video and audio signals and supports resolutions up to 3,840 x 2,160 @60Hz with full

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

colour spectrum in RGB and YCbCr 4:4:4.

Compatible with USB 3.1 and DisplayPort 1.2 standards as well as Thunderbolt 3 connections, the cable is suitable for a wide range of devices. Signal transmission is possible without additional drivers or power supplies thanks to Plug & Play and power supply via USB. This allows the cable to be used flexibly in various environments, such as home offices, training rooms or stationary workstations.

The gold-plated contacts ensure a reliable connection, even with regular use. Windows systems from version 7 and macOS from 10.9 are supported. A USB-C connection with DisplayPort Alternate Mode or a Thunderbolt 3 port is required.

Supported standards: USB 3.1, DisplayPort 1.2

Supported resolution: up to 3,840 x 2,160 @60Hz with RGB and YCbCr 4:4:4

Computers with Thunderbolt 3 are supported

For transferring video and audio signals

USB powered, no power supply required

Gold-plated contacts

Plug & Play

System requirements:

Windows 7/8/10, Mac OS 10.9 and newer

PC with a free USB-C port that supports DisplayPort Alternate Mode or PC with a free Thunderbolt 3 port